

Data Sheet | Item Number: 272-122

Power supply connector; without push-buttons; with snap-in mounting feet; without ground contact; 5-pole; white

https://www.wago.com/272-122



Color: white



Dimensions in mm

Field-wiring terminal block, 272 Series, white

Connect conductors quickly and easily with this field-wiring terminal block (item number 272-122). Conductors can only be connected to this field-wiring terminal block if their strip length is between 8 and 9 mm . This product features one conductor terminal and utilizes PUSH WIRE®. Our PUSH WIRE® connection uses the stiffness of the conductor to overcome the clamping spring's contact force, allowing you to clamp the conductor in place more quickly and easily. The dimensions are (25 x 28.5 x 30) mm (width x height x depth).

Electrical data

Ratings per	IEC/EN 60664-1		
Overvoltage category	III	III	II
Pollution degree	3	2	2
Nominal voltage	-	400 V	-
Rated impulse withstand voltage	-	4 kV	-
Rated current	-	26 A	-

Connection Data

Clamping units	20
Total number of potentials	5
Number of connection types	1

Connection 1

Connection technology	PUSH WIRE®
Strip length	8 … 9 mm / 0.31 … 0.35 inches
Pole number	5

Physical data

Width	25 mm / 0.984 inches
Height	28.5 mm / 1.122 inches
Depth	30 mm / 1.18 inches

Material data

Note (material data)	Information on material specifications can be found here
Color	white
Material group	I
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V2
Fire load	0.241 MJ
Weight	14.9 g

Commercial data

Product Group	8 (Misc. Chassis Mount Blocks)
PU (SPU)	500 pcs
Packaging type	Bag
Country of origin	DE
GTIN	4044918396820
Customs tariff number	85369010000

Product Classification

UNSPSC	39121409
eCl@ss 10.0	27-14-11-04
eCl@ss 9.0	27-14-11-04
ETIM 9.0	EC000446
ETIM 10.0	EC000446
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant,No Exemption

Approvals / Certificates

General approvals

Approval	Standard	Certificate Name
CCA DEKRA Certification B.V.	EN 60998	NTR NL 7384
CCA DEKRA Certification B.V.	EN 60998	2176190.01
CSA DEKRA Certification B.V.	C22.2 No. 158	70048844
UR Underwriters Laboratories Inc.	UL 1059	E45172

Declarations of conformity and manufacturer's declarations

Approval	Standard	Certificate Name
EU-Declaration of Conformity WAGO GmbH & Co. KG	-	-
UK-Declaration of Conformity WAGO GmbH & Co. KG	-	-

Continued on next page

Approvals for marine applications



Approval	Standard	Certificate Name
ABS American Bureau of Shipping	-	23-2417173-PDA
DNV DNV GL SE	-	TAE000016Z
LR Lloyds Register	IEC 61984	96/20035 (E5)
PRS Polski Rejestr Statków	-	TE/1095/880590/23

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 272-122

Documentation

Additional Information

Technical Section	03.04.2019	pdf 2027.26 KB

CAD/CAE-Data

CAD data

2D/3D Models 272-122

CAE data

EPLAN Data Portal 272-122

WSCAD Universe 272-122

ZUKEN Portal 272-122

Continued on next page

1 Compatible Products

1.1 Optional Accessories

1.1.1 Marking

1.1.1.1 Marking device



Item No.: 210-110
Fiber-tip pen

1.1.2 Tool

1.1.2.1 Assembly tool



Item No.: 249-100
Operating tool; for terminal blocks with snap-in ground contact