
Data Sheet | Item Number: 272-301


Power supply connector; push-button on both sides; without snap-in mounting feet; without ground contact; 1-pole; white

https://www.wago.com/272-301



Color: white

Similar to illustration



Dimensions in mm

Field-wiring terminal block, 272 Series, PUSH WIRE®

This field-wiring terminal block (item number 272-301) is designed to connect conductors quickly and easily. Conductors can only be connected to this field-wiring terminal block if their strip length is between 8 and 9 mm . This product features one conductor terminal and utilizes PUSH WIRE®. Our tried-and-tested PUSH WIRE® connection offers the fastest method for clamping conductors. It utilizes the conductor's stiffness to overcome the clamping spring's contact force. The item's dimensions are (8.5 x 19 x 24.5) mm (width x height x depth). This field-wiring terminal block is suitable for conductor cross sections ranging from 0.5 mm² to 1.5 mm² on one side and for conductor cross sections ranging from 0.5 mm² to 2.5 mm² on the other side.

Electrical data

Ratings per	IEC/EN 60664-1		
Overvoltage category	III	III	II
Pollution degree	3	2	2
Nominal voltage	-	400 V	-
Rated impulse withstand voltage	-	4 kV	-
Rated current	-	18 A	-

Connection Data

Clamping units	4
Total number of potentials	1
Number of connection types	1

Connection 1

Connection technology	PUSH WIRE®
Solid conductor	0.5 … 1.5 mm² / 20 … 16 AWG
Strip length	8 … 9 mm / 0.31 … 0.35 inches
Pole number	1

Connection 2

Solid conductor	0.5 … 2.5 mm² / 20 … 14 AWG

Continued on next page

Physical data

Width	8.5 mm / 0.335 inches
Height	19 mm / 0.748 inches
Depth	24.5 mm / 0.965 inches

Material data

Note (material data)	Information on material specifications can be found here
Color	white
Material group	I
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.046 MJ
Weight	3.1 g

Commercial data

PU (SPU)	500 pcs
Packaging type	Bag
Country of origin	DE
GTIN	4044918439497
Customs tariff number	85369010000

Product Classification

UNSPSC	39121409
eCl@ss 10.0	27-14-11-04
eCl@ss 9.0	27-14-11-04
ETIM 9.0	EC000446
ETIM 10.0	EC000446
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant,No Exemption

Approvals / Certificates

General approvals

Approval	Standard	Certificate Name
CSA DEKRA Certification B.V.	C22.2 No. 158	70048844
UR Underwriters Laboratories Inc.	UL 1059	E45172

Continued on next page

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 272-301

Documentation

Additional Information

Technical Section	03.04.2019	pdf 2027.26 KB

1 Compatible Products

1.1 Optional Accessories

1.1.1 Tool

1.1.1.1 Assembly tool



Item No.: 249-100
Operating tool; for terminal blocks with snap-in ground contact