Data Sheet | Item Number: 272-312

Power supply connector; push-button on both sides; without snap-in mounting feet; without ground contact; 12-pole; white

https://www.wago.com/272-312



Color: white

Similar to illustration



Dimensions in mm

Field-wiring terminal block, 272 Series, white

Our field-wiring terminal block (item number 272-312) ensures effortless electrical installations. Conductors can only be connected to this field-wiring terminal block if their strip length is between 8 and 9 mm . This product features one conductor terminal and utilizes PUSH WIRE®. Our PUSH WIRE® connection is the quick and easy method for connecting solid conductors. The dimensions are (118.5 x 19 x 24.5) mm (width x height x depth). This field-wiring terminal block is suitable for conductor cross sections ranging from 0.5 mm² to 1.5 mm² on one side and for conductor cross sections ranging from 0.5 mm² to 2.5 mm² on the other side.

Electrical data

Ratings per	IEC/EN 60664-1		
Overvoltage category	III	III	II
Pollution degree	3	2	2
Nominal voltage	-	400 V	-
Rated impulse withstand voltage	-	4 kV	-
Rated current	-	18 A	-

Connection Data

Clamping units	48
Total number of potentials	12
Number of connection types	1

Connection 1

Connection technology	PUSH WIRE®
Solid conductor	0.5 … 1.5 mm² / 20 … 16 AWG
Strip length	8 … 9 mm / 0.31 … 0.35 inches
Pole number	12

Connection 2

Solid conductor	0.5 … 2.5 mm² / 20 … 14 AWG

Physical data

Width	118.5 mm / 4.665 inches
Height	19 mm / 0.748 inches
Depth	24.5 mm / 0.965 inches

Material data

Note (material data)	Information on material specifications can be found here
Color	white
Material group	I
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.558 MJ
Weight	37.7 g

Commercial data

PU (SPU)	40 pcs
Packaging type	Box
Country of origin	DE
GTIN	4044918440349
Customs tariff number	85369010000

Product Classification

UNSPSC	39121409
eCl@ss 10.0	27-14-11-04
eCl@ss 9.0	27-14-11-04
ETIM 9.0	EC000446
ETIM 10.0	EC000446
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant,No Exemption

Approvals / Certificates

General approvals

Approval	Standard	Certificate Name
CSA DEKRA Certification B.V.	C22.2 No. 158	70048844
UR Underwriters Laboratories Inc.	UL 1059	E45172

Continued on next page

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 272-312

Documentation

Additional Information

Technical Section	03.04.2019	pdf 2027.26 KB

1 Compatible Products

1.1 Optional Accessories

1.1.1 Installation

1.1.1.1 Mounting accessories

Item No.: 271-702
Pins; white

Item No.: 271-711
Pins; white

Item No.: 271-712
Pins; white

1.1.2 Tool

1.1.2.1 Assembly tool



Item No.: 249-100
Operating tool; for terminal blocks with snap-in ground contact