Data Sheet | Item Number: 283-407

Power tap; with 500 mm cable; for 16 mm² (283/783 Series) and 35 mm²; gray

https://www.wago.com/283-407





Color: gray

Notes

Safety Information	Always push voltage tap down into the terminal block until fully inserted!

Electrical data

Ratings per IEC/EN

Nominal voltage (III/3)	800 V
Rated impulse withstand voltage (III / 3)	8 kV
Rated current	24 A

Material data

Note (material data)	Information on material specifications can be found here
Color	gray
Material group	I
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	15.469 MJ
Weight	22.1 g

Environmental requirements

Processing temperature	-35 … +85 °C
Continuous operating temperature	-60 … +105 °C

Commercial data

Product Group	1 (Rail Mounted Terminal Blocks)
PU (SPU)	25 pcs
Packaging type	Box
Country of origin	DE
GTIN	4044918853408
Customs tariff number	85366990990

Product Classification

UNSPSC	39121410
eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92
ETIM 9.0	EC002848
ETIM 10.0	EC002848
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant,No Exemption

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 283-407

Documentation

Bid Text

283-407	19.02.2019	xml 2.81 KB	
283-407	02.05.2017	doc 22.50 KB	

CAD/CAE-Data

CAD data

2D/3D Models 283-407

CAE data

EPLAN Data Portal 283-407

WSCAD Universe 283-407

Continued on next page

Installation Notes

Power tap



Always push voltage tap (283-407) down into the terminal block until fully inserted!