Data Sheet | Item Number: 285-168

Fixing element; for 95 mm² high-current terminal blocks; orange

https://www.wago.com/285-168



Color: orange

Material data	
Note (material data)	Information on material specifications can be found here
Color	orange
Material group	I
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.044 MJ
Weight	1.6 g

Environmental requirements	
Processing temperature	-35 … +85 °C
Continuous operating temperature	-60 … +105 °C

Commercial data	
PU (SPU)	50 (25) pcs
Packaging type	Box
Country of origin	PL
GTIN	4055143578172
Customs tariff number	39269097900

Product Classification	
UNSPSC	39121421
eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92
ETIM 9.0	EC002848
ETIM 10.0	EC002848
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant,No Exemption

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 285-168

Documentation

Bid Text

285-168	01.07.2019	xml 2.72 KB
285-168	01.07.2019	doc 22.00 KB
285-168	01.07.2019	docx 13.49 KB

CAD/CAE-Data

CAD data


2D/3D Models 285-168

CAE data

EPLAN Data Portal 285-168

Installation Notes

Installation



Optionally, insert block-to-block connector (285-168) into housing slot.



Align and snap high-current, through terminal blocks together.