
Data Sheet | Item Number: 286-307/004-000

Relay module; Nominal input voltage: 110 VDC; 1 changeover contact; Limiting continuous current: 3 A; Railway; Red status indicator; Module width: 15 mm; gray


https://www.wago.com/286-307/004-000





Color: gray

Similar to illustration



Technical data

Control circuit

Nominal input voltage U_N	110 VDC
Input voltage range	-30 … +25 %
Nominal input current at U_N	4 mA

Load circuit

Number of changeover/switchover contacts	1
Contact material (relay)	AgNi 0.15
Limiting continuous current	3 A
Switching Voltage, Max.	250 VAC
Switching power (resistive) max.	AC 750 VA
Pull-in time (typ.)	8 ms
Drop-out time (typ.)	6 ms
Bounce time (typ.)	4 ms

Continued on next page

Signaling

Status indicator	Red LED

Safety and protection

Rated Voltage	300 V
Overvoltage category	II
Pollution degree	2
Dielectric strength (control/load circuit) (AC, 1 min)	3 kVrms
Dielectric strength (open contact) (AC, 1 min)	1 kVrms
Insulation type (control/load circuit)	Reinforced insulation (safe isolation)
Insulation type (adjacent devices)	Reinforced insulation (safe isolation)
Protection type	IP20

Physical data

Width	15 mm / 0.591 inches
Height	52 mm / 2.047 inches
Depth from upper-edge of DIN-rail	82.5 mm / 3.248 inches
Note (dimensions)	Depth including carrier terminal block

Mechanical data

Mounting type	Pluggable module for receptacle terminal blocks

Material data

Note (material data)	Information on material specifications can be found here
Color	gray
Fire load	0.292 MJ
Weight	23.1 g

Environmental requirements

Ambient temperature (operation at U_N)	-25 … +70 °C
Ambient temperature (storage)	-25 … +70 °C
Processing temperature	-25 … +50 °C
Relative humidity	5 … 85 % (no condensation permissible)
Operating altitude (max.)	2000 m

Standards and Specifications

Standards/specifications	EN 61010-2-201

Commercial data

Product Group	6 (INTERFACE ELECTRONIC)
PU (SPU)	15 (1) pcs
Packaging type	Box
Country of origin	DE
GTIN	4045454709105
Customs tariff number	85364900990

Continued on next page

Product Classification

UNSPSC	39122334
eCl@ss 10.0	27-37-16-01
eCl@ss 9.0	27-37-16-01
ETIM 9.0	EC001437
ETIM 10.0	EC001437
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

CAS-No.	1303-86-2 7439-92-1 79-94-7
REACH Candidate List Substance	2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol Diboron trioxide Lead
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	7(a)
SCIP notification number (Austria)	81828017-49df-4293-a656-88ad43efb054
SCIP notification number (Belgium)	5ddc4fe6-0673-499a-8e00-c8dfe3e61a8d
SCIP notification number (Bulgaria)	08b6913c-7e63-49aa-868c-5905e8b4cd05
SCIP notification number (Czech Republic)	6fc70c82-1fab-4a89-8148-b9a659039b3a
SCIP notification number (Denmark)	af3d9c6f-763c-4fb5-8461-e5edef4dae6d
SCIP notification number (Finland)	910b84da-0a64-4266-a73b-82f0562b16e7
SCIP notification number (France)	8e409d76-c604-4f79-8e66-0310246cb279
SCIP notification number (Germany)	006dadc3-90a1-45d5-b130-4c5dc5632ff3
SCIP notification number (Hungary)	7c1acc02-2e72-4027-bf12-0cafff02106e
SCIP notification number (Italy)	e333515a-0f47-4cca-bb4c-785059621f90
SCIP notification number (Netherlands)	0c5e03ed-27b1-489b-9876-f99ccce5af3c
SCIP notification number (Poland)	6df00da0-9c65-403f-82b3-92d439f1046f
SCIP notification number (Romania)	cb548765-5811-44dc-9de0-25cb0a5d1a0e
SCIP notification number (Sweden)	3418933c-d55f-4ac5-b907-4b47107f3f03

Approvals / Certificates

General approvals

Approval	Standard	Certificate Name
EAC GZO Almaty Standart	TP TC 004/2011	EAC CoC 03078
EAC GZO Almaty Standart	TP TC 020/2011	EAC CoC 03081

Declarations of conformity and manufacturer's declarations

Approval	Standard	Certificate Name
EU-Declaration of Conformity WAGO GmbH & Co. KG	-	-

Continued on next page

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 286-307/004-000

Documentation

Instruction Leaflet

Operation and Assembly Instructions Interface	V 1.0.0 02.04.2025	pdf 1246.19 KB

CAD/CAE-Data

CAE data

WSCAD Universe 286-307/004-000

1 Compatible Products

1.1 Optional Accessories

1.1.1 Marking

1.1.1.1 Marker



Item No.: 209-701
WSB marking card; as card; not stretchable; plain; snap-on type; white

1.1.2 Terminal blocks

1.1.2.1 Terminal block for pluggable modules

Item No.: 280-619
Terminal block for pluggable modules; 6-pole; with 2-conductor terminal blocks; with orange separator; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm²; CAGE CLAMP®; 2,50 mm²; gray



Item No.: 280-763
Terminal block for pluggable modules; 6-pole; with 4-conductor terminal blocks; with marker carrier; with orange separator; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm²; CAGE CLAMP®; 2,50 mm²; gray




Item No.: 280-609
Terminal block for pluggable modules; 6-pole; with 4-conductor terminal blocks; with orange separator; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm²; CAGE CLAMP®; 2,50 mm²; gray


Continued on next page

Installation Notes

Installation




Coding ensures correct polarity.



Pluggable electronic modules on 2- or 4-conductor carrier terminal blocks

Marking



Marking via WMB Multi Marking System.

Testing



Function testing via touch-proof test slots