
Data Sheet | Item Number: 286-895


Switching module; with changeover rocker switch; Switching voltage: 250 VAC; Switching current: 6 A; gray

https://www.wago.com/286-895





Color: gray



Electrical data

Number of changeover/switchover contacts	1
Switching current (resistive) max.	6 A
Switching Voltage, Max.	250 VAC; 24 VDC
Contact gap	≥ 3 mm
Electrical life (NO; resistive load; 23 °C)	50 x 10^3 switching operations

Physical data

Width	15 mm / 0.591 inches
Height	52 mm / 2.047 inches
Depth from upper-edge of DIN-rail	85 mm / 3.346 inches
Note (dimensions)	Depth including carrier terminal block

Mechanical data

Mounting type	Pluggable module for receptacle terminal blocks
Housing design	Plug for carrier terminal blocks

Material data

Color	gray
Fire load	3.962 MJ
Weight	20.5 g

Environmental requirements

Ambient temperature (operation)	-20 … +40 °C
Relative humidity	5 … 85 % (no condensation permissible)
Operating altitude (max.)	2000 m

Commercial data

Product Group	6 (INTERFACE ELECTRONIC)
PU (SPU)	15 (1) pcs
Packaging type	Box
Country of origin	DE
GTIN	4045454399801
Customs tariff number	85365080000

Product Classification

UNSPSC	39122216
eCl@ss 10.0	27-37-16-01
eCl@ss 9.0	27-37-16-01
ETIM 9.0	EC001437
ETIM 10.0	EC001437
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

CAS-No.	7439-92-1
REACH Candidate List Substance	Lead
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	6(c)
SCIP notification number (Austria)	ba2abf80-118a-4c45-baa6-03682860db9e
SCIP notification number (Belgium)	5317ad19-2f21-4575-b952-6dad3d8fd713
SCIP notification number (Bulgaria)	948d6596-fdfb-4bb3-8c98-7e073f75efe1
SCIP notification number (Czech Republic)	9b0385e4-445e-4f89-adb2-ad11d25daa55
SCIP notification number (Denmark)	7880d7a6-e367-41db-8893-2e3324afd6d2
SCIP notification number (Finland)	7d8b079f-78b3-40f7-a068-9364adf66a90
SCIP notification number (France)	327efcd4-37ab-4034-9cd8-5f615704608e
SCIP notification number (Germany)	4e28d429-1e59-4a45-8c0b-5cc03900e93d
SCIP notification number (Hungary)	6bf0369c-53ab-4f80-a079-4945463a1621
SCIP notification number (Italy)	b795f7ba-8d61-4da3-925b-f6c501077b48
SCIP notification number (Netherlands)	152aefcd-2369-49cc-a758-d9830a4e69b7
SCIP notification number (Poland)	18fc77c5-00cf-4d89-a9b6-01a2a5b50555
SCIP notification number (Romania)	9f340bfb-951e-49c4-b163-6a2fc2bf5747
SCIP notification number (Sweden)	c694559c-24f5-4548-af7e-c0a3c4b85a76

Continued on next page

Approvals / Certificates

General approvals

Approval	Standard	Certificate Name
EAC GZO Almaty Standart	TP TC 004/2011	EAC CoC 03078

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 286-895

Documentation

Bid Text

286-895	19.02.2019	xml 2.98 KB
286-895	01.04.2015	doc 24.00 KB

Instruction Leaflet

Operation and Assembly Instructions Interface	V 1.0.0 02.04.2025	pdf 1246.19 KB

CAD/CAE-Data

CAD data

2D/3D Models 286-895

CAE data

WSCAD Universe 286-895

ZUKEN Portal 286-895

1 Compatible Products

1.1 Optional Accessories

1.1.1 Marking

1.1.1.1 Marker



Item No.: 209-701
WSB marking card; as card; not stretchable; plain; snap-on type; white

Continued on next page

1.1.2 Terminal blocks

1.1.2.1 Terminal block for pluggable modules

Item No.: 280-619
Terminal block for pluggable modules; 6-pole; with 2-conductor terminal blocks; with orange separator; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm²; CAGE CLAMP®; 2,50 mm²; gray



Item No.: 280-763
Terminal block for pluggable modules; 6-pole; with 4-conductor terminal blocks; with marker carrier; with orange separator; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm²; CAGE CLAMP®; 2,50 mm²; gray



Item No.: 280-609
Terminal block for pluggable modules; 6-pole; with 4-conductor terminal blocks; with orange separator; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm²; CAGE CLAMP®; 2,50 mm²; gray