

Data Sheet | Item Number: 289-111

Component module with diode; with 14 pcs; Diode 1N4007; with common cathode; 2,50 mm²

https://www.wago.com/289-111





Notes

Safety Information	**Notice!** Accessible live parts! Protection against accidental contact must be provided by the system installer, e.g., using a WAGO 709 Series Cover (see "Accessories") or a similar cover. The installation guidelines must be followed for each specific application.
Note	Max. permissible forward current per the manufacturer's data sheet. With all diodes loaded, the continuous current must be reduced to 0.45 A.

Electrical data

Operating voltage	≤ 250 VAC/VDC
Peak reverse voltage	1000 V
Type of diode	1N4007; with common cathode
Number/type of diode/LED	14 diodes
Rectified current for each diode (resistive)	1 A
Forward voltage per diode	1.1 V
Forward current per diode (resistive)	1 A
Leakage current	50 µA

Safety and protection

Rated Voltage	250 V
Rated impulse withstand voltage	4 kV
Pollution degree	2
Protection type	IP00

Connection Data

Note (conductor cross-section)	12 AWG: THHN, THWN

Connection 1

Connection technology	CAGE CLAMP®
WAGO connector	WAGO 236 Series
Solid conductor	0.08 … 2.5 mm² / 28 … 12 AWG
Fine-stranded conductor	0.08 … 2.5 mm² / 28 … 12 AWG
Strip length	5 … 6 mm / 0.2 … 0.24 inches

Physical data

Width	42.5 mm / 1.673 inches
Height from the surface	32 mm / 1.26 inches
Depth	62.5 mm / 2.461 inches

Mechanical data

Mounting type	Mounting on DIN-rail via DIN-rail adapter
Housing design	PCB

Material data

Weight	25.6 g

Environmental requirements

Ambient temperature (operation)	-25 … +40 °C

Commercial data

Product Group	6 (INTERFACE ELECTRONIC)
PU (SPU)	50 (1) pcs
Packaging type	Box
Country of origin	DE
GTIN	4045454192761
Customs tariff number	85369010000

Product Classification

UNSPSC	39121629
eCl@ss 10.0	27-14-11-27
eCl@ss 9.0	27-14-11-49
ETIM 9.0	EC000903
ETIM 10.0	EC000903
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

CAS-No.	7439-92-1 79-94-7
REACH Candidate List Substance	2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol Lead
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	7(a)
SCIP notification number (Austria)	8d3ff2d5-b591-4e51-9d39-3424bd391e82
SCIP notification number (Belgium)	96ca9689-b508-42b9-ab5e-d3f67dfc8da6
SCIP notification number (Bulgaria)	0f8b4f87-cf19-4f7b-aee3-fcc1dbf31127
SCIP notification number (Czech Republic)	4b291d39-5af9-4a09-9048-2a8203e2a22f
SCIP notification number (Denmark)	8d9f09f2-bdd5-422e-96b4-ba0912a74ea7
SCIP notification number (Finland)	e7fa87ba-32e0-4249-ab19-73bc2a29ff9c
SCIP notification number (France)	b9c1b78a-9ae4-4e56-a5fa-dce4db66dc0f
SCIP notification number (Germany)	7f7d7235-33e7-4211-ac4d-e29c8b42f806
SCIP notification number (Hungary)	577067a2-858d-489f-b5a0-dbc75d281d4d
SCIP notification number (Italy)	10e53c66-3123-4983-9c39-b29252731b82
SCIP notification number (Netherlands)	031570be-fff6-494d-80c6-b4f25ffc2768
SCIP notification number (Poland)	d13d8daa-9727-47b7-ab67-d8297a04c70f
SCIP notification number (Romania)	2f93e3af-a5ce-4c3c-9825-14bd894cea3b
SCIP notification number (Sweden)	00b21fbc-11e1-401a-b0de-79d58c6b567d

Continued on next page

Approvals / Certificates

General approvals

Approval	Standard	Certificate Name
EAC GZO Almaty Standart	TP TC 004/2011	EAC CoC 03084

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 289-111

Documentation

Bid Text

289-111	11.02.2015	doc 25.00 KB
289-111	19.02.2019	xml 3.50 KB

Instruction Leaflet

Operation and Assembly Instructions Interface	V 1.0.0 02.04.2025	pdf 1246.19 KB

CAD/CAE-Data

CAE data

EPLAN Data Portal 289-111

WSCAD Universe 289-111

1 Compatible Products

1.1 Optional Accessories

1.1.1 Ferrule

1.1.1.1 Ferrule



Item No.: 216-321
Ferrule; Sleeve for 0.25 mm² / AWG 24; insulated; electro-tin plated; yellow

Item No.: 216-322
Ferrule; Sleeve for 0.34 mm² / 22 AWG; insulated; electro-tin plated; light turquoise

Item No.: 216-221
Ferrule; Sleeve for 0.5 mm² / 20 AWG; insulated; electro-tin plated; white

Item No.: 216-222
Ferrule; Sleeve for 0.75 mm² / 18 AWG; insulated; electro-tin plated; gray

Item No.: 216-223
Ferrule; Sleeve for 1 mm² / AWG 18; insulated; electro-tin plated; red



Item No.: 216-224
Ferrule; Sleeve for 1.5 mm² / AWG 16; insulated; electro-tin plated; black

Continued on next page

1.1.2 Installation

1.1.2.1 Cover



Item No.: 709-153
Cover; Type 1; suitable for cover carrier, type 1; 1 m long; transparent

1.1.2.2 Cover carrier



Item No.: 709-167
Cover carrier; Type 1; incl. fixing/retaining screws and knurled nut; suitable for 279 to 282 and 880 Series rail-mounted terminal blocks; suitable for 264 Series miniature rail-mounted terminal blocks; suitable for 270 Series sensor and actuator terminal blocks; gray

1.1.2.3 Mounting carrier and mounting feet



Item No.: 288-001
Mounting carrier; gray



Item No.: 288-002
Universal mounting foot; snap-fit type; suitable for DIN 15, 35 and 32 rails; gray

1.1.3 Marking

1.1.3.1 Marking strip



Item No.: 210-831
Marking strips; on reel; 2.3 mm wide; plain; Self-adhesive; white



Item No.: 210-832
Marking strips; on reel; 3 mm wide; plain; Self-adhesive; white

1.1.4 Tool

1.1.4.1 Operating tool



Item No.: 210-720
Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; multicoloured