
Data Sheet | Item Number: 294-5022

Lighting connector; push-button, external; without ground contact; N´-L´; 2-pole; Lighting side: for solid conductors; Inst. side: for all conductor types; max. 2.5 mm²; Surrounding air temperature: max 85°C (T85); white

https://www.wago.com/294-5022





Color: white

Dimensions in mm

Field-wiring terminal block, 294 Series, push-button

Connect conductors quickly and securely with this field-wiring terminal block (item number 294-5022). Strip lengths must be between 8 and 9 mm when connecting conductors to this field-wiring terminal block. Featuring four conductor terminals along with Push-in CAGE CLAMP® as well as PUSH WIRE®, this product is highly versatile. Our Push-in CAGE CLAMP® is a universal, maintenance-free connection solution for all conductor types, boasting a key feature: both solid and fine-stranded conductors with ferrules can be directly inserted without the need for tools or any preparation, such as crimping the ferrule. Our proven PUSH WIRE® connection offers the fastest method for clamping conductors. It utilizes the conductor's stiffness to overcome the clamping spring's contact force. Dimensions: (20 x 21.53 x 27.3) mm (width x height x depth). Depending on the type of conductor, this field-wiring terminal block is designed for conductor cross sections ranging from 0.5 mm² to 2.5 mm² on one side and for conductor cross sections from 0.5 mm² to 2.5 mm² on the other side as well as conductor cross sections from 0.5 mm² to 1.5 mm² and from 0.5 mm² to 0.75 mm².

The contact surface is coated with tin.

Electrical data

Ratings per	IEC/EN 60998-1		
Overvoltage category	III	III	II
Pollution degree	3	2	2
Nominal voltage	-	-	500 V
Rated impulse withstand voltage	-	-	4 kV
Rated current	-	-	24 A

Ratings per IEC/EN – Notes	
Ratings (note)	Connection points

Ratings per	IEC/EN 60998-2-2		
Overvoltage category	III	III	II
Pollution degree	3	2	2
Nominal voltage	-	-	500 V
Rated impulse withstand voltage	-	-	4 kV
Rated current	-	-	24 A

General information	
Wiring direction	Side-entry wiring

Connection Data

Clamping units	10
Total number of potentials	2
Number of connection types	4
PE function	without PE contact

Connection 1

Connection type	External 1
Connection technology	Push-in CAGE CLAMP®
Number of connection points	2
Actuation type	Push-button
Connectable conductor materials	Copper
Solid conductor	0.5 … 2.5 mm² / 18 … 12 AWG
Solid conductor; push-in termination	0.5 … 2.5 mm² / 18 … 12 AWG
Stranded conductor	0.5 … 2.5 mm² / 18 … 14 AWG
Fine-stranded conductor	0.5 … 2.5 mm² / 18 … 14 AWG
Fine-stranded conductor; with insulated ferrule	0.5 … 1.5 mm² / 18 … 16 AWG
Fine-stranded conductor; with uninsulated ferrule	0.5 … 1.5 mm² / 18 … 16 AWG
Fine-stranded conductor; with ferrule; push-in termination	0.5 mm² / 18 AWG
Strip length	8 … 9 mm / 0.31 … 0.35 inches
Pole number	2
Wiring direction	Side-entry wiring

Connection 2

Connection type	Internal 2
Connection technology	PUSH WIRE®
Number of connection points	1
Actuation type	Push-in
Solid conductor	0.5 … 2.5 mm² / 18 … 14 AWG
Fine-stranded conductor; with insulated ferrule	0.5 … 1 mm² / 18 … 16 AWG
Fine-stranded conductor; with uninsulated ferrule	0.5 … 1.5 mm² / 18 … 14 AWG
Strip length	8 … 9 mm / 0.31 … 0.35 inches

Connection 3

Connection type	Internal 3
Connection technology	PUSH WIRE®
Number of connection points	1
Actuation type	Push-in
Solid conductor	0.5 … 1.5 mm² / 18 … 16 AWG
Fine-stranded conductor; with insulated ferrule	0.5 … 0.75 mm² / 18 AWG
Fine-stranded conductor; with uninsulated ferrule	0.5 … 1 mm² / 18 AWG
Strip length	8 … 9 mm / 0.31 … 0.35 inches

Connection 4

Connection type	Internal 4
Connection technology	PUSH WIRE®
Number of connection points	1
Actuation type	Push-in
Solid conductor	0.5 … 0.75 mm² / 18 AWG
Strip length	8 … 9 mm / 0.31 … 0.35 inches

Physical data

Pin spacing	10 mm / 0.394 inches
Width	20 mm / 0.787 inches
Height	21.53 mm / 0.848 inches
Height from the surface	17 mm / 0.669 inches
Depth	27.3 mm / 1.075 inches

Continued on next page

Mechanical data

Marking	N´-L´
Mounting type	Snap-in foot

Material data

Note (material data)	Information on material specifications can be found here
Color	white
Material group	IIIa
Insulation material (main housing)	Polycarbonate (PC)
Flammability class per UL94	V0
Clamping spring material	Chrome-nickel spring steel (CrNi)
Contact material	Electrolytic copper (E_{Cu})
Contact Plating	Tin
Fire load	0.094 MJ
Halogen-free	Yes
Weight	6.4 g

Environmental requirements

Temperature stability	120 °C
T marking	T85

Commercial data

Product Group	8 (Misc. Chassis Mount Blocks)
PU (SPU)	1000 pcs
Packaging type	Foil
Country of origin	CH
GTIN	4050821098188
Customs tariff number	85369010000

Product Classification

UNSPSC	39121402
eCl@ss 10.0	27-14-11-06
eCl@ss 9.0	27-14-11-06
ETIM 9.0	EC001284
ETIM 10.0	EC001284
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant,No Exemption
SCIP notification number (Austria)	8c5d3053-0c99-43ca-86ed-1842d4f67a3c
SCIP notification number (Belgium)	f7b2c190-831b-485c-b9e9-cfaaed9010c1
SCIP notification number (Bulgaria)	ef045ad6-e74b-4eac-b86c-4cd6e72030cc
SCIP notification number (Czech Republic)	c230a102-85ad-486d-9782-a268b385bd0f
SCIP notification number (Denmark)	77db38b1-5f7e-4687-a1fb-a67c03bb0cbf
SCIP notification number (Finland)	4c689c64-1464-46f4-b377-68a11622f020
SCIP notification number (France)	b7a310ab-7e72-4b79-a46c-dcc916932fde
SCIP notification number (Germany)	9cd06e77-23e4-4521-aefa-d36be54ccf9c
SCIP notification number (Hungary)	885410d9-2e5d-4a97-b971-00a60a7c1719
SCIP notification number (Italy)	4eeb9b62-4b56-4c61-a7ed-c2390a149bfa
SCIP notification number (Netherlands)	94ce3a6b-94e4-4d83-a136-2b9a7f0033e3
SCIP notification number (Poland)	ac8e9858-f081-45d0-ae84-28c7ea205e60
SCIP notification number (Romania)	40427a66-a5d1-4836-b1b8-5d779fa2e2e4

Continued on next page

Environmental Product Compliance

SCIP notification number (Sweden)	9664d724-c14b-4eb7-b075-8bcc5ce170d6

Approvals / Certificates

General approvals

Approval	Standard	Certificate Name
ENEC 05 DEKRA Certification B.V.	EN 60998	2128791.01

Declarations of conformity and manufacturer's declarations

Approval	Standard	Certificate Name
EU-Declaration of Conformity WAGO GmbH & Co. KG	-	-
UK-Declaration of Conformity WAGO GmbH & Co. KG	-	-

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 294-5022

Documentation

Bid Text

294-5022	19.02.2019	xml 5.58 KB
294-5022	13.06.2017	doc 27.00 KB

CAD/CAE-Data

CAD data

2D/3D Models 294-5022

CAE data

WSCAD Universe 294-5022

ZUKEN Portal 294-5022

Continued on next page

1 Compatible Products

1.1 Optional Accessories

1.1.1 Strain relief

1.1.1.1 Strain relief



Item No.: 294-370
Strain relief; for 294 Series; with snap-in mounting feet; white



Item No.: 294-375
Strain relief; for 294 Series; without snap-in mounting feet; white

1.1.1.2 Strain relief plate



Item No.: 294-364
Strain relief plate; for 294 Series; for multi-core cables; 3- to 5-pole; with secured clamp; white



Item No.: 294-384
Strain relief plate; for 294 Series; for single strands; 3- to 5-pole; with secured clamp; white

1.1.2 Tool


1.1.2.2 Operating tool




Item No.: 206-294
Disconnection tool; green

Installation Notes


Installation



2-pole – without ground contact




Snap-in foot



Drilled hole for snap-in mounting foot

Conductor termination





EUROPE	
1 x 0.5 … 2.5 mm² "s"	
1 x 0.5 … 1.5 mm² "s"	
1 x 0.5 … 0.75 mm² "s"	
AMERICA	
1 x AWG 18 … 14 "s"	
1 x AWG 18 … 16 "s"	
1 x AWG 18 "s"	
JAPAN	
1 x 0.8 … 1.6 mm diam. "s"	
1 x 0.8 … 1 mm diam. "s"	
1 x 0.8 mm diam. "s"	

Internal connection:
PUSH WIRE® for internal wiring with solid conductors

EUROPE	
2 x 0.5 … 2.5 mm² "s, str, f-str"	
AMERICA	
2 x AWG 18 … 12 "s"	
2 x AWG 18 … 14 "s, f-str"	
JAPAN	
2 x 0.8 … 2 mm diam. "s"	
2 x 0.5 … 2 mm² "str, f-str"	

External connection:
Push-in CAGE CLAMP® for field-wiring with all conductor types





Terminating five conductors per pole – solid and fine-stranded.

