Data Sheet | Item Number: 706-3057/300-300

System cable; for Schneider TSX; 16 digital inputs or outputs; Length: 3 m; Conductor cross-section: 0.14 mm²

https://www.wago.com/706-3057/300-300









Color coding acc. to DIN VDE 47100		Interface connector		PLC connector	
		Pin number	Wiring	Pin number	Signal
White		1	0.0	1	IN/OUT1
Brown		2	0.1	2	IN/OUT2
Green		3	0.2	3	IN/OUT3
Yellow		4	0.3	4	IN/OUT4
Grey		5	0.4	5	IN/OUT5
Pink		6	0.5	6	IN/OUT6
Blue		7	0.6	7	IN/OUT7
Red		8	0.7	8	IN/OUT8
Black		9	1.0	9	IN/OUT9
Violet		10	1.1	10	IN/OUT10
Grey-Pink		11	1.2	11	IN/OUT11
Red-Blue		12	1.3	12	IN/OUT12
White-Green		13	1.4	13	IN/OUT13
Brown-Green		14	1.5	14	IN/OUT14
White-Yellow		15	1.6	15	IN/OUT15
Yellow-Brown		16	1.7	16	IN/OUT16
White-Grey		17	+24V	17	Alim+
Grey-Brown		18	0V	18	Alim-
White-Pink		19	+24V	19	Alim+
Pink-Brown		20	0V	20	Alim-

Short description:

WAGO's Interface Cables provide fast and easy connection of WAGO I/O Modules equipped with a 20-pole pluggable connector (750-1400, -1402, -1500, -1501, -1502) to the appropriate interface or relay modules (16-channel) featuring a 20-pole pluggable connector.
The cables are available in 1-, 2- and 3-meter lengths; each has one 20-pole pluggable connector at both ends.

Notes

Note	When using more than 10 wires, the maximum current per wire must be reduced to 0.7 A.

Electrical data

Inputs/outputs	16 digital inputs or outputs
Operating voltage	≤ 35 VAC/VDC
Current per wire (max.)	1 A

Compatibility

Schneider

Schneider Modicon Quantum	140 DDI 364 00 140 DDO 364 00
Schneider TSX	TSX DEY 16FK TSX DEY 32D2K TSX DEY 64D2K TSX DEZ 12D2K TSX DMY 28FK TSX DMY 28RFK TSX DMZ 28DTK TSX DMZ 64DTK TSX DSY 32T2K TSX DSY 64T2K

WAGO

WAGO I/O System 750	750-1400 750-1500 750-1502

Connection Data

Cable type	LiYY
Color code	per DIN VDE 47100

Connection 1

Pluggable connector	Pluggable connector per DIN 41651; female connector
Pole number 1	20
Connection type	System
Wire cross-section	0.14 mm²

Connection 2

Connector	Pluggable connector per DIN 41651; female connector
Pole number	20
Connection type	System
Wire cross-section	0.14 mm²

Physical data

Cable length	3 m

Material data

Weight	231.4 g

Continued on next page

Environmental requirements

Ambient temperature (operation)	-20 … +50 °C

Commercial data

Product Group	30 (WAGO France)
PU (SPU)	1 pcs
Packaging type	not specified
Country of origin	FR
GTIN	4045454873783
Customs tariff number	85444290900

Product Classification

UNSPSC	26121629
eCl@ss 10.0	27-06-03-11
eCl@ss 9.0	27-06-03-11
ETIM 9.0	EC000237
ETIM 10.0	EC000237
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant,No Exemption

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 706-3057/300-300

Documentation

Bid Text

706-3057/300-300	26.11.2018	docx 14.75 KB	
706-3057/300-300	19.02.2019	xml 3.41 KB	

CAD/CAE-Data

CAE data

WSCAD Universe 706-3057/300-300

Continued on next page

1 Compatible Products

1.1 Optional Accessories

1.1.1 Interface module

1.1.1.1 Interface module



Item No.: 704-2004
Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel digital input or output; 1-wire connection; in mounting carrier



Item No.: 704-2024
Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel digital input or output; 2-wire connection; in mounting carrier



Item No.: 704-2044
Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel digital input or output; 2-wire connection; in mounting carrier



Item No.: 704-2054
Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel digital input or output; 3-wire connection; in mounting carrier



Item No.: 704-5004
Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel relay output; 1 changeover contact; Double-deck PCB terminal blocks; in mounting carrier; 2,50 mm²



Item No.: 704-5014
Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel relay output; 1 changeover contact; Double-deck PCB terminal blocks; without relay; in mounting carrier; 2,50 mm²



Item No.: 704-5034
Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel relay output; 1 changeover contact; PCB terminal blocks; with output fuse; in mounting carrier; 2,50 mm²



Item No.: 704-5024
Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel relay output; 1 changeover contact; Triple-deck PCB terminal blocks; in mounting carrier; 2,50 mm²



Item No.: 704-5044
Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel relay output; 1 changeover contact; Triple-deck PCB terminal blocks; with manual operation; in mounting carrier; 2,50 mm²



Item No.: 704-5054
Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel relay output; 1 make contact; with disconnect terminal block and fuse; in mounting carrier; 2,50 mm²



Item No.: 704-5074
Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel relay output; 1 make contact; with disconnect terminal block and fuse; in mounting carrier; 2,50 mm²



Item No.: 704-5064
Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel relay output; 2 changeover contacts; Double-deck PCB terminal blocks; in mounting carrier; 2,50 mm²



Item No.: 289-614
Interface module; Pluggable connector per DIN 41651; 20-pole; Triple-deck PCB terminal blocks; in mounting carrier; 2,50 mm²