

Data Sheet | Item Number: 709-170

Disconnect lock; for disconnect tab used on 280/281 and 769 Series disconnect terminal blocks; red

<https://www.wago.com/709-170>



Color: ■ red

Material data	
Note (material data)	Information on material specifications can be found here
Color	red
Fire load	0.023 MJ
Weight	0.8 g

Commercial data	
Product Group	2 (Terminal Block Accessories)
PU (SPU)	200 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4017332812412
Customs tariff number	39269097900

Product Classification	
UNSPSC	39121702
eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92
ETIM 9.0	EC002848
ETIM 10.0	EC002848
ECCN	NO US CLASSIFICATION



Environmental Product Compliance	
RoHS Compliance Status	Compliant, No Exemption

Downloads

Environmental Product Compliance

Compliance Search


Environmental Product Compliance 709-170

↓

Documentation			
Bid Text			
709-170	19.02.2019	xml 2.55 KB	↓
709-170	28.04.2017	doc 23.00 KB	↓

CAD/CAE-Data	
CAD data 2D/3D Models 709-170 ↓	CAE data WSCAD Universe 709-170 ↓

Installation Notes



Double Safety:
The disconnect tab has been designed for maximum operational safety.

As soon as the disconnect tab is in the disconnect position, it can be protected against unintentional reconnection by using the disconnect lock.
Only through intentional and deliberate use of a tool, can the disconnect lock be removed and the circuit reconnected.

Features/Benefits:

- Easy to use
- Install/remove disconnect lock with just one hand
- Clearly identify disconnect tab position
- Higher safety
- Intentional effort is required to reconnect the circuit

Installation



Installing a disconnect lock on the terminal block's disconnect tab.



Unlocking a disconnect lock.



Removing a disconnect lock.