

Data Sheet | Item Number: 855-305/250-501


Plug-in current transformer; Primary rated current: 250 A; Secondary rated current: 5 A;

Rated power: 5 VA; Accuracy class: 1


<https://www.wago.com/855-305/250-501>




Similar to illustration



Dimensions in mm



Dimensions in mm



Short description:

WAGO's plug-in current transformers (855 Series) are inductive, single-conductor current transformers. Due to the measurement principle used, these current transformers are exclusively designed for AC network applications.

Features:

- Screwless CAGE CLAMP® connection technology
- Several mounting options available
- Vibration- and shock-resistant
- High mechanical retention forces
- High current-carrying capacity
- Continuous overload of 120 % the nominal primary current
- Low-voltage current transformer for operating voltages up to max. 1.2 kV
- For 690 V power networks
- UL recognized components

Technical data

Input		Input – current transformer	
Measured variable	Current	Rated continuous thermal current I_{cth}	$1.2 \times I_N$
		Rated short-time thermal current I_{th}	$60 \times I_N / 1 \text{ s}$ (max. 100 kA / 1 s)
		Overcurrent limiting factor	FS5 / FS10 (type dependent; see type plate inscription)
		Rated frequency	50 ... 60 Hz
		Primary rated current	250 A
Output – current transformer		Measurement Error	
Secondary rated current	5 A	Accuracy class	1
Rated power S_r	5 VA		

Safety and protection		
Test voltage	6 kVAC; 50 Hz; 1 min	
Highest voltage for equipment U_m	1.2 kV _{rms} AC	

Connection Data		
Feedthrough for measurement conductor	Ø 26 mm	Connection 1
		Connection technology
		CAGE CLAMP®
		Strip length
		9 ... 10 mm / 0.35 ... 0.39 inches
		Solid conductor
		0.08 ... 4 mm ² / 28 ... 12 AWG
		Fine-stranded conductor
		0.08 ... 4 mm ² / 28 ... 12 AWG

Physical data	
Width	60 mm / 2.362 inches
Height	80.9 mm / 3.185 inches
Depth	52 mm / 2.047 inches

Mechanical data	
Mounting type	Closed current transformer Installation on mounting plate Mounting on DIN-rail via DIN-rail adapter Installation on round cable

Material data	
Insulation class	E
Weight	333 g

Environmental requirements		
Ambient temperature (operation)		-5 ... +50 °C
Ambient temperature (storage)		-25 ... +70 °C
Operating altitude (max.)		1000 m

Standards and Specifications		
Conformity marking		CE
Standards/specifications		EN 61869-1 EN 61869-2 UL: E356480

Commercial data		
PU (SPU)		1 pcs
Packaging type		Box
Country of origin		HU
Customs tariff number		85043129900

Product Classification		
UNSPSC		39121032
eCl@ss 10.0		27-21-09-02
eCl@ss 9.0		27-21-09-02
ETIM 9.0		EC002048
ETIM 10.0		EC002048
ECCN		NO US CLASSIFICATION

Environmental Product Compliance		
RoHS Compliance Status		Compliant, No Exemption

Approvals / Certificates

General approvals



Approval	Standard	Certificate Name
EAC	TP TC 004/2011	EAC CoC 03082
GZO Almaty Standart		
UL	IEEE C57.13	E356480
Underwriters Laboratories Inc.		

Declarations of conformity and manufacturer's declarations

Approval	Standard	Certificate Name
EU-Declaration of Conformity WAGO GmbH & Co. KG	-	-
UK-Declaration of Conformity WAGO GmbH & Co. KG	-	-

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance

855-305/250-501

↓

Documentation

Bid Text

855-305/250-501

19.02.2019

xml

4.95 KB

↓

855-305/250-501

05.02.2015

doc

31.00 KB

↓

Instruction Leaflet

Aufsteck-Stromwandler

pdf

1438.11 KB

↓

CAD/CAE-Data

CAD data

2D/3D Models

855-305/250-501

↓

CAE data

EPLAN Data Portal

855-305/250-501

↓

WSCAD Universe

855-305/250-501

↓

ZUKEN Portal

855-305/250-501

↓

1 Compatible Products

1.1 Optional Accessories

1.1.1 Installation

1.1.1.1 Current transformer terminal block



Item No.: 2007-8876

Compact terminal block; for 3-phase current transformer circuit; 6,00 mm²; multicoloured



Item No.: 2007-8873

Compact terminal block; for current and voltage transformers; 6,00 mm²; multi-coloured



Item No.: 2007-8874

Compact terminal block; for current and voltage transformers; 6,00 mm²; multi-coloured



Item No.: 2007-8875

Compact terminal block; for current transformer circuit; 6,00 mm²; multicoloured



Item No.: 2007-8877

Compact terminal block; for current transformer circuit; 6,00 mm²; multicoloured

1.1.2 Mounting adapter

1.1.2.1 DIN-rail adapter



Item No.: 855-9900
Carrier rail adapter

1.1.2.2 Fast connection adapter



Item No.: 855-9910
Quick-mount kit

1.1.3 Signal conditioner

1.1.3.1 Current Signal Conditioner



Item No.: 857-551
Current signal conditioner; Current input signal; Current and voltage output signal; Digital output; Configuration via software; Supply voltage: 24 VDC; 6 mm module width



Item No.: 857-550
Current signal conditioner; Current input signal; Current and voltage output signal; Digital output; Configuration via software; Supply voltage: 24 VDC; 6 mm module width; 2,50 mm²

1.1.3.2 Power Measurement Module



Item No.: 2857-570/024-005
3-Phase Power Measurement Module; 3x277/480 V/5 A; Modbus RTU; Digital output; Configuration via software; Supply voltage: 24 VDC



Item No.: 857-569
Power signal conditioner; Current and voltage input signal; Current and voltage output signal; Digital output; Configuration via software; Supply voltage: 24 VDC; 6 mm module width

1.1.4 Tool


1.1.4.1 Operating tool




Item No.: 210-720
Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; multicoloured

Installation Notes


Installation



Installation on copper current bar




Installation on round cable




Installation on mounting plate



Mounting on DIN-rail via 855-9900 DIN-Rail Adapter



Snapping onto DIN-rail



Snapping onto DIN-rail



Installation via 855-9910 Quick-Mount Kit

Conductor termination



Conductor termination – screwdriver actuation perpendicular to conductor entry



Conductor termination – screwdriver actuation parallel to conductor entry