


Data Sheet | Item Number: 857-409

Isolation amplifier; Bipolar current and voltage input signal; Bipolar current and voltage output signal; Zero/span adjustment; Configuration via DIP switch; Supply voltage: 24 VDC; 6 mm module width; 2,50 mm²

https://www.wago.com/857-409







857-409

DIP Switch Adjustability

● = ON Default

DIP Switch S1 (4-fold)					DIP Switch S2 (6-fold)							
Input Signal					Output Signal						Max. Operating Frequency	
1	2	3	4		1	2	3	4	5		6	
●				±20 mA				●		±20 mA		5 kHz
●	●			±10 mA			●	●		±10 mA	●	100 Hz
●				±10 V	●	●		●		±10 V		
●	●			±5 V	●	●	●	●		±5 V		
				0 ... 20 mA						0 ... 20 mA		
		●		4 ... 20 mA					●	4 ... 20 mA		
	●			0 ... 10 mA			●			0 ... 10 mA		
	●	●		2 ... 10 mA			●		●	2 ... 10 mA		
				0 ... 10 V	●	●				0 ... 10 V		
		●		2 ... 10 V	●	●			●	2 ... 10 V		
	●			0 ... 5 V	●	●	●			0 ... 5 V		
	●	●		1 ... 5 V	●	●	●		●	1 ... 5 V		

Short description:

WAGO's bipolar signal conditioner converts standard unipolar/bipolar signals, as well as amplifies, filters and electrically isolates the bipolar standard analog signals.

Features:

- Overload protection of current input via resettable fuse
- Zero/span adjustment across the entire measurement range
- Calibrated measurement range switching
- Unipolar/bipolar standard analog signals at both input/output
- Switchable limit frequency

Notes

Safety Information	Input and output must be safely isolated from any hazardous live parts!
Note	**Use shielded signal cables!** Only use shielded signal cables for analog input and output signals. This ensures the device maintains its specified accuracy and immunity to interference, even when external disturbances affect the signal cable. Use in residential areas is only permitted in conjunction with a power supply that meets the residential area criteria according to EN 61000-6-3.

Technical data

Configuration

Configuration options	DIP switch Potentiometer

Input

Input signal type	Voltage Current
Input signal (voltage)	±5 V 0 … 5 V 1 … 5 V ±10 V 0 … 10 V 2 … 10 V
Input signal (current)	±10 mA 0 … 10 mA 2 … 10 mA ±20 mA 0 … 20 mA 4 … 20 mA
Input resistance (current input)	≤ 50 Ω
Input resistance (voltage input)	1 MΩ
Input current (max.)	50 mA
Input voltage (max.)	32 V
Zero/span adjustment	±5 % of upper range value

Output (analog)

Output signal type	Current Voltage
Output signal (voltage)	±5 V 0 … 5 V 1 … 5 V ±10 V 0 … 10 V 2 … 10 V
Output signal (current)	±10 mA 0 … 10 mA 2 … 10 mA ±20 mA 0 … 20 mA 4 … 20 mA
Load impedance (voltage output)	≥ 2 kΩ
Load impedance (current output)	≤ 600 Ω
Residual ripple	≤ 10 mV (rms)

Signal Processing

Limit frequency	100 Hz / 5 kHz (configurable via DIP switch)
Step response (typ.)	3.5 ms (100 Hz) 68 µs (5 kHz)

Measurement Error

Transmission error (typ.)	≤ 0.1 % of upper-range value
Transmission error (max.)	≤ 0.2 % of upper-range value
Transmission error (under interference)	≤ 15 %
Temperature coefficient	≤ 0.01 %/K

Power Supply

Power supply type	24 VDC (SELV)
Nominal supply voltage U_S	24 VDC
Supply voltage range	±30 %
Current consumption (default)	≤ 20 mA
Current consumption (max.)	≤ 40 mA

Continued on next page

Safety and protection

Rated Voltage	300 V
Protection type	IP20

Test voltage

Test voltage (input/output/supply)	3 kVAC; 50 Hz; 1 min

Insulation coordination

Overvoltage category	II
Pollution degree	2
Insulation type (input/analog output/supply)	Functional insulation
Insulation type (adjacent devices)	Reinforced insulation (safe isolation)

Connection Data

Connection technology	Push-in CAGE CLAMP®
Solid conductor	0.08 … 2.5 mm² / 28 … 14 AWG
Fine-stranded conductor	0.34 … 2.5 mm² / 22 … 14 AWG
Strip length	9 … 10 mm / 0.35 … 0.39 inches
Cable type	Shielded cable

Physical data

Width	6 mm / 0.236 inches
Height	94 mm / 3.701 inches
Depth from upper-edge of DIN-rail	97.8 mm / 3.85 inches

Mechanical data

Mounting type	DIN-35 rail

Material data

Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.488 MJ
Weight	39.2 g

Environmental requirements

Ambient temperature (operation)	-25 … +70 °C
Ambient temperature (storage)	-40 … +85 °C
Processing temperature	-25 … +50 °C
Temperature range of connection cable	≥ ($T_{ambient}$ + 10 K)
Relative humidity	5 … 95 % (no condensation permissible)
Operating altitude (max.)	2000 m

Continued on next page

Standards and Specifications

Conformity marking	CE
EMC immunity to interference	EN 61000-6-2
EMC emission of interference	EN 61000-6-3
Standards/specifications	EN 61010-1 EN 61373 DNV

Commercial data

Product Group	6 (INTERFACE ELECTRONIC)
PU (SPU)	1 pcs
Packaging type	Bag
Country of origin	DE
GTIN	4045454828493
Customs tariff number	85437090300

Product Classification

UNSPSC	32101502
eCl@ss 10.0	27-21-01-20
eCl@ss 9.0	27-21-01-20
ETIM 9.0	EC002653
ETIM 10.0	EC002653
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

CAS-No.	1303-86-2 1317-36-8 7439-92-1 75980-60-8
REACH Candidate List Substance	Diboron trioxide Lead Lead monoxide Phosphine oxide, diphenyl(2,4,6-trimethylbenzoyl)-
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	6(c) 7(a) 7(c)-I 7(c)-II 7c
SCIP notification number (Austria)	3045ef60-f28a-43e4-9dba-b63435d5553d
SCIP notification number (Belgium)	8f1d744b-8731-4270-a640-73cf63782d7f
SCIP notification number (Bulgaria)	74cd0cd4-d3cc-4fa9-ac76-5a1ca5bb11a1
SCIP notification number (Czech Republic)	0689176b-e48c-48ed-859f-591c9a9bb606
SCIP notification number (Denmark)	ffd652f9-d5f2-45bf-981b-f0fde66c585f
SCIP notification number (Finland)	7c145b78-dbc2-4260-85cc-22a468112985
SCIP notification number (France)	3a00d327-3185-4fcb-a0b8-36a561c46061
SCIP notification number (Germany)	15951163-bfc4-44d4-b679-9146fa50b484
SCIP notification number (Hungary)	5fd6a05b-6f43-463e-8f9a-4ab07da40dfd
SCIP notification number (Italy)	ea8b18af-ed6a-4f27-b024-7378eb0f2d3d
SCIP notification number (Netherlands)	56e8430c-ad8e-4e3a-b6f2-897614bc0f79
SCIP notification number (Poland)	62fe04e8-fd16-49c4-be93-f76f40eef9e0
SCIP notification number (Romania)	01c54ad8-3056-427f-8fc0-0b8e8c12d949
SCIP notification number (Sweden)	4527d706-aff0-40c4-95f8-d5d44d48a189

Continued on next page

Approvals / Certificates

General approvals

Approval	Standard	Certificate Name
EAC GZO Almaty Standart	TP TC 020/2011	EAC CoC 03081
UL Underwriters Laboratories Inc. (ORDINARY LOCATIONS)	UL 508	E175199 Sec.4

Declarations of conformity and manufacturer's declarations

Approval	Standard	Certificate Name
EU-Declaration of Conformity WAGO GmbH & Co. KG	-	-
UK-Declaration of Conformity WAGO GmbH & Co. KG	-	-

Approvals for marine applications

Approval	Standard	Certificate Name
DNV DNV Germany GmbH	DNV-CG-0339,Aug.2021	TAA00001D1
PRS Polski Rejestr Statków	-	TE/1098/880590/23

Approvals for hazardous areas

Approval	Standard	Certificate Name
ATEX TUEV Nord Cert GmbH	EN 60079-0	TUEV14ATEX112692X (II 3G Ex ec IIC T4 Gc)
CCC CNEX	CNCA-C23-01	2020312310000210 (Ex ec IIC T4 Gc)
IECEx TUEV Nord Cert GmbH	-	IECEX TUN14.0030X
UKEx WAGO GmbH & Co. KG	EN 60079-0	WAGO22UKEX004X
UL Underwriters Laboratories Inc. (HAZARDOUS LOCATIONS)	ANSI/ISA 12.12.01	E198726

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 857-409

Documentation

Manual

WAGO Isolating Amplifiers

Bid Text

857-409	18.07.2019	xml 6.15 KB
857-409	18.07.2019	docx 18.48 KB
857-409	18.07.2019	pdf 74.80 KB

Continued on next page

Instruction Leaflet		
CCC Ex (Additional information)	26.04.2023	pdf 140.99 KB
Trennverstärker; bipolares Strom- und Spannungseingangssignal; bipolares Strom- und Spannungsausgangssignal	V 2.1.0 07.04.2022	pdf 2111.32 KB

CAD/CAE-Data

CAD data
2D/3D Models 857-409

CAE data
EPLAN Data Portal 857-409
WSCAD Universe 857-409
ZUKEN Portal 857-409

1 Compatible Products

1.1 Optional Accessories

1.1.1 Installation

1.1.1.1 Mounting accessories



Item No.: 249-117
Screwless end stop; 10 mm wide; for DIN-rail 35 x 15 and 35 x 7.5; gray



Item No.: 249-197
Screwless end stop; 14 mm wide; for DIN-rail 35 x 15 and 35 x 7.5; gray



Item No.: 249-116
Screwless end stop; 6 mm wide; for DIN-rail 35 x 15 and 35 x 7.5; gray

1.1.2 Interface module

1.1.2.1 Interface adapters



Item No.: 857-980
Interface adapter; 16-pole; analog

1.1.3 Jumper

1.1.3.1 Jumper



Item No.: 281-482
Jumper; 2-way; insulated; gray



Item No.: 859-410/000-006
Jumper; for jumper slot; 10-way; insulated; blue



Item No.: 859-410
Jumper; for jumper slot; 10-way; insulated; light gray



Item No.: 859-410/000-005
Jumper; for jumper slot; 10-way; insulated; red



Item No.: 859-410/000-029
Jumper; for jumper slot; 10-way; insulated; yellow



Item No.: 859-402/000-006
Jumper; for jumper slot; 2-way; insulated; blue



Item No.: 859-402
Jumper; for jumper slot; 2-way; insulated; light gray



Item No.: 859-402/000-005
Jumper; for jumper slot; 2-way; insulated; red

Continued on next page

1.1.3.1 Jumper



Item No.: 859-402/000-029
Jumper; for jumper slot; 2-way; insulated; yellow



Item No.: 859-403/000-006
Jumper; for jumper slot; 3-way; insulated; blue



Item No.: 859-403
Jumper; for jumper slot; 3-way; insulated; light gray



Item No.: 859-403/000-005
Jumper; for jumper slot; 3-way; insulated; red



Item No.: 859-403/000-029
Jumper; for jumper slot; 3-way; insulated; yellow



Item No.: 859-404/000-006
Jumper; for jumper slot; 4-way; insulated; blue



Item No.: 859-404
Jumper; for jumper slot; 4-way; insulated; light gray



Item No.: 859-404/000-005
Jumper; for jumper slot; 4-way; insulated; red



Item No.: 859-404/000-029
Jumper; for jumper slot; 4-way; insulated; yellow



Item No.: 859-405/000-006
Jumper; for jumper slot; 5-way; insulated; blue



Item No.: 859-405
Jumper; for jumper slot; 5-way; insulated; light gray



Item No.: 859-405/000-005
Jumper; for jumper slot; 5-way; insulated; red



Item No.: 859-405/000-029
Jumper; for jumper slot; 5-way; insulated; yellow



Item No.: 859-406/000-006
Jumper; for jumper slot; 6-way; insulated; blue



Item No.: 859-406
Jumper; for jumper slot; 6-way; insulated; light gray



Item No.: 859-406/000-005
Jumper; for jumper slot; 6-way; insulated; red



Item No.: 859-406/000-029
Jumper; for jumper slot; 6-way; insulated; yellow



Item No.: 859-407/000-006
Jumper; for jumper slot; 7-way; insulated; blue



Item No.: 859-407
Jumper; for jumper slot; 7-way; insulated; light gray



Item No.: 859-407/000-005
Jumper; for jumper slot; 7-way; insulated; red



Item No.: 859-407/000-029
Jumper; for jumper slot; 7-way; insulated; yellow

Item No.: 859-408/000-006
Jumper; for jumper slot; 8-way; insulated; blue

Item No.: 859-408
Jumper; for jumper slot; 8-way; insulated; light gray

Item No.: 859-408/000-005
Jumper; for jumper slot; 8-way; insulated; red

Item No.: 859-408/000-029
Jumper; for jumper slot; 8-way; insulated; yellow

Item No.: 859-409/000-006
Jumper; for jumper slot; 9-way; insulated; blue

Item No.: 859-409
Jumper; for jumper slot; 9-way; insulated; light gray

Item No.: 859-409/000-005
Jumper; for jumper slot; 9-way; insulated; red

Item No.: 859-409/000-029
Jumper; for jumper slot; 9-way; insulated; yellow

1.1.4 Marking

1.1.4.1 Marker

Item No.: 793-5501
WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; white



Item No.: 793-502
WMB marking card; as card; MARKED; 1 ... 10 (10x); not stretchable; Horizontal marking; snap-on type; white



Item No.: 793-566
WMB marking card; as card; MARKED; 1 ... 50 (2x); not stretchable; Horizontal marking; snap-on type; white

Item No.: 793-503
WMB marking card; as card; MARKED; 11 ... 20 (10x); not stretchable; Horizontal marking; snap-on type; white

Item No.: 793-504
WMB marking card; as card; MARKED; 21 ... 30 (10x); not stretchable; Horizontal marking; snap-on type; white

Item No.: 793-505
WMB marking card; as card; MARKED; 31 ... 40 (10x); not stretchable; Horizontal marking; snap-on type; white

Item No.: 793-506
WMB marking card; as card; MARKED; 41 ... 50 (10x); not stretchable; Horizontal marking; snap-on type; white

Item No.: 793-501
WMB marking card; as card; not stretchable; plain; snap-on type; white



Item No.: 2009-115
WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white

Continued on next page

1.1.4.2 Marking strip



Item No.: 2009-110
Marking strips; for Smart Printer; on reel; not stretchable; plain; snap-on type; white

1.1.5 Power supply

1.1.5.1 Power Supply



Item No.: 787-2852
Switched-mode power supply; 1-phase; 24 VDC output voltage; 1 A output current

1.1.6 Terminal blocks

1.1.6.1 Supply and through module



Item No.: 857-979
Supply and through module

1.1.7 Tool


1.1.7.1 Operating tool



Item No.: 210-720
Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; multicoloured


Installation Notes

Configuring



Configuration via DIP switch

Commoning



Commoning, not discrete wiring – Same out-line allows use of a single in-line, push-in jumper.

 Continued on next page