

Start Waterproof START WATERPROOF 1200 HOUSING 2X 0047923



Caratteristiche prodotto

- Luminaire, polycarbonate housing • Twin version, 1200mm • Protection type IP65 • Luminous flux and light colour vary depending on LED tubes used • To be used with T8 LED tubes • Easy to install with stainless steel fixing brackets included for ceiling mounting • Ideal for any industrial facilities, garages, car parks, workshops.



PANORAMICA DEL PRODOTTO

Nome prodotto	START WATERPROOF 1200 HOUSING 2X
Tecnologia	LED
Cap/Base	G13
Housing	PC Polycarbonate
Montaggio	Ceiling surface mounting
Fixture rating	Chiuso
General application	Logistics & Industry
ETIM Class	EC002892
E-number Finlandia	4309057
Garanzia	3 years
L.O.R. (%)	75
Lampada inclusa	N/A - Not Applicable
Electrical protection	Classe I
Colore corpo lampada	Grigio
IP rating	IP65
IK rating	IK08
Product EAN number	5410288479231

TABELLA DATI

Dati generali

Nome prodotto	START WATERPROOF 1200 HOUSING 2X
Tecnologia	LED
Cap/Base	G13
Housing	PC Polycarbonate
Montaggio	Ceiling surface mounting
Fixture rating	Chiuso
General application	Logistics & Industry
ETIM Class	EC002892
E-number Finlandia	4309057
Garanzia	3 years

Dati ottici

Start Waterproof START WATERPROOF 1200 HOUSING 2X 0047923

L.O.R. (%)	75
------------	----

Dati elettrici

Lampada inclusa	N/A - Not Applicable
Electrical protection	Classe I
Glow Wire Test (°C)	650

Dati dimensionali

Colore corpo lampada	Grigio
IP rating	IP65
IK rating	IK08
Diffuser finish	Transparent
Diffuser material	PC Polycarbonate
Lunghezza nominale del prodotto (mm)	1260
Larghezza nominale prodotto (mm)	99
Nominal Product Height (mm)	78
Peso (Kg)	1.11

Dati di imballo

Tipologia imballo singolo	Carton
Product EAN number	5410288479231
Lunghezza imballo singolo (mm)	128.0
Larghezza imballo singolo (cm)	9.9
Packaging single depth (cm)	5.2
DUN14 (outer)	15410288479238
Quantità per imballo esterno	1
Packaging outer length / height (cm)	128.0
Packaging outer width (cm)	9.9
Packaging outer depth (cm)	5.2

DISEGNI TECNICI

