


**POOL SAND FILTER SYSTEM**

- Multi-way valve with five functions: filtering, backwashing, rinsing, draining, closing
- Stable filter tank with a diameter of 330 mm and 26 litres capacity
- 20 kg silica sand (Ø 0.45-0.55 mm) or 600 g filter balls act as the filter medium
- Effective filter surface 0.08 m<sup>2</sup>
- 550 watt pump mounted on a stable base plate
- Connection size 1.5"
- Pump performance 13,800 L/h at 550 watts / 220 – 240 V~
- Suitable for water temperatures of 4 °C up to 43 °C
- Delivery contents: multi-way valve, locking flange, pressure gauge, filter tank, swimming pool pump, base plate, connection set and sand filling aid



INCLUDED



**SPECIFICATIONS**

Max. delivery height	11 m
Max. filter capacity	13,800 L/h
Effective filter surface	0.08 m <sup>2</sup>
Filter tank	26 L
Engine power	550 W

**LOGISTICAL DATA**

Weight net / gross	10.1 / 12.1 kg
Packaging dimensions	550 x 355 x 625 mm
Article number	5910002902
Barcode	4046664161943
20 Container	262 pcs
40 Container	537 pcs
40 HQ Container	615 pcs




**EXAMPLES OF USE SUITABLE FOR**

Above-ground pool



Fixed pools with maintenance flap



**Five-way valve**

Filtering, emptying, closed, backflushing, rinsing



Includes filling aid for the filter material

**Integrated pressure display** shows the current pressure in the sand filter. Is also used to measure the degree of contamination and perform cleaning if required.

**PRODUCT DETAILS**

Max. delivery height 11 m



Max. filter capacity 13,800 litres per hour



550 Watt pump



26 litre filter tank (Filter material: silica sand 20 kg or filter balls 600 g)



Max. operating pressure of 2.4 bar



Effective filter surface 0,08 m<sup>2</sup>

