## **ELECTRIC**

## PSFA26

## POOL SAND FILTER SYSTEM

- Multi-way valve with five functions: filtering, backwashing, rinsing, draining, closing
- Stable filter tank with a diameter of 330 mm and 26 litres capacity
- + 20 kg silica sand (Ø 0.45-0.55 mm) or 600 g filter balls act as the filter medium
- Effective filter surface 0.08 m<sup>2</sup>
- 550 watt pump mounted on a stable base plate
- · Connection size 1.5"
- Pump performance 13800 L/h at 550 watts / 220 240 V~
- Suitable for water temperatures of 4 °C up to 43 °C
- · Delivery contents: multi-way valve, locking flange, pressure gauge, filter tank, swimming pool pump, base plate, connection set



## SPECIFICATIONS

CLU

Max. delivery height Max. pump performance Effective filter surface Filter tank Input

11 m 13800 L/h 0.08 m<sup>2</sup> 26 L 550 W

LOGISTICAL DATA	
Weight net / gross	10.1 / 12.1 kg
Packaging dimensions	550 x 355 x 625 mm
Article number	5910002902
Barcode	4046664161943
20 Container	262 pcs
40 Container	537 pcs
40 HQ Container	615 pcs

www. styped .com | Issue 2022-07-26 | Subject to technical change without notice. Errors and omissions excepted.