



INCLUDED

SPECIFICATIONS

Dimensions L x W x H	588 x 842 x 746 mm
Blade Ø	305 mm
Motor speed	5000 rpm
Bevel type	2 x 48°
Mitre capacity	-50° left till +50° right
Cross cut at 90° / 90°	340 x 105 mm
Mitre cut at 90° / 45°	340 x 35 mm (r.) 340 x 60 mm (l.)
Bevel cut at 45° / 90°	240 x 105 mm
Compound cut at 45° / 45°	240 x 60 mm (r.) 240 x 60 mm (l.)
Mitre slots	45-31.6-22.5-0-22.5-31.6-45°
Motor	220 – 240 V~ / 50 Hz
Engine power	2000 W

305 MM SLIDING CROSS-CUT MITRE SAW WITH SLIDING PULLOUT FUNCTION

- High-performance 2000 Watt motor with soft start function
- Saw head can be angled 48° to either side for professional results
- Work table can be adjusted from -50° to +50°
- Sliding pullout function with parallel guides requires no space behind the unit
- Built-in laser for precise cutting along the indicated cutting edge
- 305 mm carbide saw blade for consistent and precise cutting results
- High cutting capacity of 340 mm width and 105 mm height
- Thanks to the special cutting height extension, a height of 180 mm at a maximum width of 20 mm can be sawn – ideal for skirting or tongue-and-groove boards
- Saw blade fully enclosed by guard for maximum work safety
- Includes carbide saw blade with 48 teeth


LOGISTICAL DATA

Weight net / gross	20.9 / 24.6 kg
Packaging dimensions	750 x 585 x 390 mm
Article number	5901223901
Barcode	4046664161035
20 Container	162 pcs
40 Container	320 pcs
40 HQ Container	360 pcs



EXAMPLES OF USE  
SUITABLE FOR

Skirting




Laminate/  
panelling




Timber joists



Paving



Angular cuts




SPECIAL FEATURES



PRODUCT DETAILS

Cutting width/height



Special cutting height



Blade Ø 305 x 30 mm  
48 teeth



Soft start



2000 W



220 – 240 V~ / 50 Hz



Laser



Compact design

