

CORDLESS ANGLE GRINDER

- Powerful cordless angle grinder for cutting, deburring or polishing
- Cordless work with the Scheppach IXES 20 Volt series – all batteries and chargers belonging to this system series can be combined with the cordless angle grinder
- Slim housing design with soft-grip and aluminium front allows working in narrow areas
- Integrated soft-start and protection against overload ensure a long service life
- Protective shatter-proof cover can be adjusted without the need for tools
- Speed adjustment from 2500 to 10,000 rpm in 6 steps using a setting wheel – for operation to suit the material and application
- 3-position front handle with storage compartment for assembly key and non-slip soft-grip ensures increased comfort and safety
- Easy tool replacement, thanks to spindle lock
- M14 tool holder and 125 mm disc diameter
- Battery and charger available separately
- Includes 1x 125 mm cutting wheel, 1x two-hole assembly key, 1x 3-position front handle



3-position front handle with non-slip soft-grip

Spindle lock

Ergonomic compact design with rubberised housing ensures comfortable operation

Battery and charger available separately



LOGISTICAL DATA

Weight net / gross	1.7 / 2.3 kg
Packaging dimensions	410 x 175 x 115 mm
Article number	5909234900
Barcode	4046664216476
20 Container	2680 pcs
40 Container	5600 pcs
40 HQ Container	6600 pcs

SPECIFICATIONS

Dimensions L x W x H	395 x 240 x 115 mm
Motor type	Brush motor
Nominal speed	2500 – 10,000 rpm
Grinding disc Ø	125 mm
Tool holder	M14
Locking function	Spindle lock
Battery voltage	20 V



EXAMPLES OF USE
SUITABLE FOR

Workshop



Construction site



House



Garden



Slim housing design with soft-grip and aluminium front allows working in narrow areas.



Protective shatter-proof cover can be adjusted without the need for tools.



Easy tool replacement, thanks to spindle lock.



Speed adjustment in 6 steps using a setting wheel


Storage compartment for a two-hole assembly key

PRODUCT DETAILS

Protection against overload



Ø 125 mm



Speed
2500 – 10,000 rpm



20 V



3-position front handle with non-slip soft-grip.



UNIVERSAL USE



CUTTING



GRINDING



DEBURRING