



Petrol engine with e-starter

Electric Start

MINI EXCAVATOR

- Mini excavator with an operating weight of 563.5 kg and compact design for a range of excavation work
- High-performance 8.5 horsepower/6.3 kW 4-stroke petrol engine, 306 cc
- Rotation speed of the excavator: 9.3 rpm / Rotation range: 360°
- Swivelling range of the boom: +/- 70°
- Digging force of the boom: 4.2 kN / Digging force of the bucket: 8.8 kN
- Loading height: max. 1,350 mm / Discharge height: max. 2,100 mm / Digging depth: max. 1,200 mm / Reach: max. 2,330 mm
- 690 mm track width – ideal for narrow passages and for reaching areas that are difficult to access
- Large levelling blade that can be lowered to support the boom or to move soil
- Chain drive: Rubber tracks with a width of 150 mm, can be individually controlled
- Speed max. 1.7 km/h
- Equipped as standard with a 290 mm wide bucket with 0.011 m³ capacity
- E-starter for easy start-up of the excavator
- Climbing ability max. 15°



SPECIFICATIONS	
Dimensions L x W x H	690 x 2210 x 1585 mm
Bucket width	290 mm
Bucket capacity	0,011 m³
Digging force of the arm	4,2 kN (485 kg)
Digging force of the bucket	8,8 kN (815 kg)
Speed	1,7 km/h
Ground contact pressure	26,5 kPa (0,27 kg/cm²)
Swivelling speed	7,5 min ⁻¹
Rotation range	360°
Power output	306 cc / 8,5 HP / 6,3 kW

SPECIFICATION	
Max. digging depth	1200 mm
Max. reach	2330 mm
Max. discharge height	2100 mm
Max. loading height	1350 mm

LOGISTICAL DATA	
Weight net / gross	562 / 685 kg
Packaging dimensions	2300 x 760 x 1300 mm
Article number	5915001903
Barcode	4046664249177
40 HQ Container	32 pcs



EXAMPLES OF USE

Garden



Construction site



Bucket capacity: 0,011 m³
Bucket width: 290 mm



Large levelling blade that can be lowered to support the boom or to move soil.



Climbing ability max. 15°



Swivelling range of the boom: +/- 70°



690 mm track width – ideal for narrow passages and for reaching areas that are difficult to access.



Thanks to the extensive digging reach of max. 2,330 mm, work can also be carried out on slopes or inclines.



PRODUCT DETAILS

Speed 1,7 km/h



Bucket width 290 mm




Climbing ability max. 15°



Track width 690 mm



4-stroke petrol engine
306 cc / 8,5 HP / 6,3 kW



Rotation range 360°

