

1/2" CORDLESS SCREWDRIVER – SET

BC-IW1350-X – SET L



BRUSHLESS

PRODUCT DATA	
Dimensions L x W x H	230 x 230 x 95 mm
Engine type	Brushless motor
Battery voltage	20 V
Torque max.	1356 Nm / 1898 Nm in anti-clockwise rotation
Nominal idle speed	0 – 650 rpm 0 – 1250 rpm 0 – 1550 rpm
Number of impacts	0 – 500 bpm 0 – 1500 bpm 0 – 1900 bpm
Retainer	1/2"
Quick-stop function:	Yes
LED	Yes

→ 150 / 400 / 1356 Nm
← 1898 Nm

0 – 650 rpm
0 – 1250 rpm
0 – 1550 rpm

0 – 500 bpm
0 – 1500 bpm
0 – 1900 bpm

1/2" receiver

Quick-Stop function

20 V

Part of the battery platform

20VIXES

ONE BATTERY FOR ALL DEVICES

+

+

2.4 A

Battery-Set

4.0 Ah

Loosening bolts: 17 mm width across flats

2.0 Ah	4.0 Ah
600 pcs.	1200 pcs.

Specification per battery charge
Running time and performance may vary depending on external conditions.

Wide range of applications thanks to 4 adjustable torque settings with 150 Nm, 400 Nm, 1356 Nm and 1898 Nm.

1/2 inch receiver with friction ring for a secure fit and easy attachment changes.

Includes 3 sockets (17, 19, 21 mm), 1/2 inch to 3/4 inch bit adapter and belt clip.

Practical belt clip – ideal for working on a ladder.

With clockwise and anti-clockwise rotation function.

UNIVERSAL APPLICATION

Quick-stop function that can be switched on and off in anti-clockwise rotation – the device switches off as soon as the screw is loosened to prevent it from falling.

High performance thanks to a torque of up to 1356 Nm and a loosening torque of up to 1898 Nm.

INCLUDING

• Socket (17 mm)
• Socket (19 mm)
• Socket (21 mm)
• 1/2" adapter
• Belt clip

• 1x 20 V / 4.0 Ah battery
• 1x 2.4 A battery charger

