



PRODUCT DATA	
Angle grinder dimensions L x W x H	395 x 240 x 115 mm
Engine type	Brush motor
Battery voltage	20 V / 2.0 Ah Lithium
Power battery charger	230 – 240 V~ / 50 Hz / 2.4 A
Rated speed	2500 – 10,000 rpm
Disc Ø	125 mm
Tool receiver	M14
Lock function	Spindle lock
Soft start	Yes
Overload protection	Yes

LOGISTICAL DATA	
Weight net / gross	3.2 / 6.2 kg
Packaging dimensions	390 x 175 x 340 mm
Item number	5909356900
EAN	4046664290292
20 containers	1050 pcs.
40 containers	2210 pcs.
40 HQ containers	2600 pcs.

UNIVERSAL APPLICATION



Cutting off



Sanding



Deburring



3-position front handle with non-slip soft grip.



Slim housing design with soft grip and aluminium front allows for working in tight spaces.



Speed adjustment from 2500 to 10,000 rpm in 6 steps via an adjustment wheel.



Storage compartment for the two-hole mounting key.



Easy tool change thanks to spindle lock.

Cutting performance: Round pipe Ø 12 mm	
2.0 Ah	4.0 Ah
65 cuts	130 cuts
Specification per battery charge Running time and performance may vary depending on external conditions	



Tool-free adjustable, burst-proof protective hood.

1.7 kg

Mobil

15-part accessory set

SOFT START

Overload protection

20 V

INCLUDING

- 10x cutting wheels (1 mm)
- 3x roughing discs (6 mm)
- 2x flat discs

- 1x cordless angle grinder
- 1x 2.4 A battery charger
- 1x 20 V / 2.0 Ah battery

