

Scheppach BASA3

Oberklasse 1,3

Heimwerker Praxis 1/22

Preis/Leistung: sehr gut

Testsieger

Heimwerker Praxis 1/22

360°

306 mm

205 mm

VARIO DRIVE

schneppach

Triple roller guidance

Cast iron table (standard)

Base frame (standard)

12" PROFESSIONAL BAND SAW

- Unique vario drive adjustable from 370 to 750 m/min
- Sturdy cast-iron table tiltable from -8° to +45°
- Triple roller precision blade guidance system above and below the table
- Balanced and ground band wheels with rubber facing
- Quick-clamping lever for saw blade
- Maximum cutting height: 205 mm
- Throat 306 mm
- Precision fence with magnified scale which can be set both left and right of saw blade
- Base frame with wheel kit included

2 power settings

220 – 240 V~ / 50 Hz	400 V~ / 50 Hz
1100 W	1100 W

QUICK CLAMPING SYSTEM

Quick-lock clamping system for minimum down time when changing bandsaw blade.

Cutting height adjustment using hand wheel.

Leg stand with wheel kit included. Note the convenient pull out handle for easy manoeuvrability.

INCLUDED

LOGISTICAL DATA		
Weight net / gross	79 / 84.5 kg	
Packaging dimensions	1150 x 620 x 420 mm	
Article number	1901503901 (230 V)	1901503902 (400 V)
Barcode	4014915079019	4014915079026
20 Container	72 pcs	
40 Container	144 pcs	
40 HQ Container	180 pcs (with palette)	

SPECIFICATIONS		
Dimensions L x W x H	610 x 1030 x 1660 mm	
Table size	548 x 400 mm	
Table adjustment	-8° – 45°	
Band wheel diameter	315 mm	
Saw blade length	2360 mm	
Cutting speed	370 – 750 m/min	
Thickness capacity / width	205 / 306 mm	
Motor	220 – 240 V~	400 V
Input	1100 W	

APPLICATIONS

Ripping

Angular cut

Curved cut

PRODUCT DETAILS

Cutting height

205 mm

Throat

306 mm

Saw band length

2360 mm

Saw band width

3.5 – 16 mm

Vario drive

370 – 750 m/min

Band wheel diameter

315 mm

Precision fence with magnified scale. Can be used on the left or on the right side of the saw blade.

EXAMPLES OF USE

Both softwood and hardwood can be easily processed with the BASA3.

Even delicate work can be effortlessly implemented, thanks to the different saw band widths.

VARIO DRIVE

Unique vario drive. Adjustable speeds from 370 to 750 m/min.

Angle adjustment using tilt unit

-8° – +45°

Triple roller precision blade guidance system. Fitted above and below table.