PLC40 PLC40 **ELECTRIC ELECTRIC** 



## PLASMA CUTTER

- Powerful compact device with robust housing and carrying handle
- For precise and clean through-cutting operations up to a material thickness
- · Can be used for straight and circular cutting operations on copper, stainless steel, aluminium, iron, and steel
- Freely adjustable cutting current (from 15 to 40 A)
- High-quality plasma cutting torch with hose package and exchangeable torch
- 2 m grounding cable with a strong clamp
- Compressed air hose with quick connecting system
- Compatible with industry-standard compressors
- Including 3 nozzles, 3 electrodes (1 pre-assembled each) and compressed air hose with quick connecting system

SPECIFICATIONS	
Dimensions L x W x H	375 x 169 x 250 mm
Cutting current	15 – 40 A
Mains connection	230 V~ / 50 Hz
Cutting performance (depending on material)	Copper 1 – 4 mm Stainless steel 1 – 8 mm Aluminium 1 – 8 mm Iron 1 – 10 mm Steel 1 – 12 mm
Working pressure	4 – 4.5 bar

LOGISTICAL DATA	
Weight net / gross	6 / 7.4 kg
Packaging dimensions	435 x 272 x 305 mm
Article number	5906605901
Barcode	4046664095446
20 container	600 pcs
40 container	1200 pcs
40 HQ container	1400 pcs

## **EXAMPLES OF USE** SUITABLE FOR Stainless steel Brass Sheet Iron Aluminium Copper (balcony railing) (sheet steel) (tap) AL





Separation cuts up to 12 mm

Compatible with conventional compressors





Overheating protection No gas required





Lightweight



Transportable





