

NEW

# PELER 8

The smart and multifunctional air cooler, for longer lasting comfort



## MOTORIZED FLAP

To vertically direct the air flow



## TOUCH DISPLAY

LED display and touch controls



## 8 LT TANK

Large water tank for longer duration



## INTEGRATED IONIZER

The technology that makes air cleaner.



## INTEGRATED TIMER

Automatic shut-down programmable up to 12 hrs



## REMOTE CONTROL INCLUDED

For even simpler management

## FEATURES

- Maximum power absorption: W 75
- Air Flow (max): 400 m<sup>3</sup>/h
- Maximum air speed: 7 m/s
- Maximum sound power level:  57 dB (A)
- Large water tank capacity: 8 lt
- LED display and touch controls
- Motorized flaps to vertically direct the air flow
- Automatic swing of horizontal airflow
- Integrated ionizer
- Remote control included
- Integrated timer up to 12 hrs
- 3 fan speeds
- Wheels for an easy transportation

			PELER 8
PRODUCT CODE			99311
EAN CODE			8021183993110
Supply voltage		V/ph/Hz	220-240 / 1 / 50- 60
Maximum power absorption		W	75
Stand-by power consumption		W	-
Fan speeds		n	3
Air volume (maximum)		m³/h	400
Air speed (maximum)		m/s	7,0
Sound pressure level (1)		dB (A)	-
Maximum Sound power level (1)		dB (A)	 57
Degree of protection provided by covers			-
Insulation class			II
Power cable		n / mm²	2 x 0,75
Water tank capacity		l	8,0
Evaporative sheet			honeycomb
Control panel			Display Touch
Maximun remote control range ( distance / angle )		m	-
Conformity Mark			CE-LVD/EMC/GS/ROHS/ERP
Certification Mark			TUV
Product size (W x H x D)		mm	380 x 735 x 300
Gift box size (W x H x D)		mm	410 x 725 x 330
Weight (without packaging)		Kg	6,5
Weight (with packaging)		Kg	7,5
Units per master box		n	-
Master size (W x H x D)		mm	-
Timer			Up to 12 hours
Removable water tank			✓
Oscillating function			YES
Remote control			✓
Ionizer			✓
Wall support			-
Power off switch			-
Power supply cable housing			-

(1) Test condition: The sound pressure level is measured in half-anechoic room far 2 meters from the front of the appliance with the microphone at 1 meter of height. During the test, all the appliance functions are enabled with the exception of swing function (if available).