



- Classic light bulb shape ensures an easy replacement
- Instant 100% light when switched on and no startup time
- No UV / IR radiance so there is less risk of damage



## Specifications

Item Code	Item Description	Equivalent to (W)	Power (W)	Lumen	Efficacy (lm/W)	CCT (K)	Weight (kg/pc)
500010000500	Mini Globe (P, G45), Dimmable (Triac) LED-E-P45-FILA-E14-2.8W-DIM-2700K-FR	GLS 25W		250	89	2700	0.02

## Packaging Information

Item			Box			
Item Code	Item Description	EU HS Code	Dimensions (mm) (LxWxH)	Gross Weight (kg)	EAN	pc/box
500010000500	LED-E-P45-FILA-E14-2.8W-DIM-2700K-FR	85395200	45x45x91	0.04	6945730405265	1
821017001200	LEDSmart-BLE-Relay-250W-DIM	94059200	90x40x30	0.08	6941408898469	1
821017003600	LEDSmart-BLE2-Relay-250W-DIM	94059200	90x40x30	0.09	6931783007594	1

Technical Specifications		Electrical Supply	
Lifetime (L70)	15,000 h	Frequency	50/60 Hz
On-/Off-cycles	100,000	Nominal voltage	220-240 V
Dimmability	Triac	DC input voltage	No
Beam angle	360°	<b>Ambient Conditions</b>	
Finishing	Frosted	Operating temperature	-20-+40°C
Colour rendering index (CRI)	> 80	Application temperature	+25°C
		Storage environment	-25-+50°C



**ENERGY**

OPPLE Lighting  
500010000500


A	B	C	D	E	F	G

F

**3** kWh/1000h

2019/2015

## Dimensional Drawing (mm)



## Photometric Data

