



Filament

- Classic light bulb shape ensures an easy replacement
- Instant 100% light when switched on and no startup time
- No UV / IR radiance so there is less risk of damage



Specifications

Item Code	Item Description	Equivalent to (W)	Power (W)	Lumen	Efficacy (lm/W)	CCT (K)	Weight (kg/pc)
500010001100	LED-E-A60-FILA-E27-4.5W-DIM-2700K-CL	GLS 40W		470	104	2700	0.03

Packaging Information

Item			Box			
Item Code	Item Description	EU HS Code	Dimensions (mm) (LxWxH)	Gross Weight (kg)	EAN	pc/box
500010001100	LED-E-A60-FILA-E27-4.5W-DIM-2700K-CL	85395200	128x68x68	0.08	6945730405340	1
821017001200	LEDsmart-BLE-Relay-250W-DIM	94059200	90x40x30	0.08	6941408898469	1
821017003600	LEDsmart-BLE2-Relay-250W-DIM	94059200	90x40x30	0.09	6931783007594	1

Technical Specifications		Electrical Supply	
Lifetime (L70)	15,000 h	Frequency	50/60 Hz
On-/Off-cycles	100,000	Nominal voltage	220-240 V
Dimmability	Triac	DC input voltage	No
Beam angle	360°	Ambient Conditions	
Finishing	Clear	Operating temperature	-20-+40°C
Colour rendering index (CRI)	> 80	Application temperature	+25°C
		Storage environment	-25-+50°C



ENERGY

OPPLE Lighting
500010001100

A	
B	
C	
D	
E	
F	
G	


F

5 kWh/1000h

2019/2015

Dimensional Drawing (mm)

LED-E-A60-FILA



Photometric Data

