



- Waterproof housing for use with LED TL tubes (not-included)
- Flexible wiring options on side and backside
- Future-proof solution due to serviceability and upgradability of lamps
- Equipped with 3x15mm² throughwiring



Specifications

Item Code	Item Description	Weight (kg/pc)
Housing (excluding light source)		
531001001900	LEDWaterproof-CLA Housing L600-T8-1x	0.37

Packaging Information


Item			Box			
Item Code	Item Description	EU HS Code	Dimensions (mm) (LxWxH)	Gross Weight (kg)	EAN	pc/box
531001001900	LEDWaterproof-CLA Housing L600-T8-1x	94051190	691x70x63	0.58	6931783027912	1

Technical Specifications		Electrical Supply	
Beam angle	120°	Frequency	50/60 Hz
Finishing	Grey RAL 7035	Nominal voltage	220-240 V
Degree of protection (IP)	IP65	DC input voltage	No
Impact strength	IK08	Mechanical Properties	
Power factor	≥ 0.9	Material housing	Polycarbonate
Input wire diameter	1mm ² - 2.5mm ²	UV resistant	Yes
Internal wiring (mm ²)	3x2.5	Optical material	Polycarbonate
Max. input cable diameter (mm)	7-11.5 mm	Mounting clips	Stainless steel



Dimensional Drawing (mm)

LEDWaterproof-CLA Housing L600-T8-1x



Installation Possibilities

