



Slim Panel Basic G3

- Suitable for recessed and suspended applications
- Recessed ceiling frame and surface module kit available as accessory



Specifications

Item Code	Item Description	Equivalent to (W)	Power (W)	Lumen	Efficacy (lm/W)	UGR	CCT (K)	Beam angle	Weight (kg/pc)
542003096700	LEDPanelS-B3 Sq620-32W-830-U19	TL 4x18W	32	3630	115	≤19	3000	90°	2.13

Accessories

 542003021800 LEDPanelRc-S-B2 Mounting-Springs	 542003021700 LEDPanelRc-S-B2 Suspension-Kit	 542098030700 Junction-Box-WH	 542098000800 LEDPanelRC-SI U19 EM-kit 1h	 542098000900 LEDPanelRC-SI U19 EM-kit 3h	 140060852 LEDFixture-Ceiling-Cable- Kit-0.5m
--	--	--	---	---	---

Packaging Information

Item			Box			
Item Code	Item Description	EU HS Code	Dimensions (mm) (LxWxH)	Gross Weight (kg)	EAN	pc/box
542003096700	LEDPanelS-B3 Sq620-32W-830-U19	94051190	670x40x625	2.76	6941497771384	1
140060852	LEDFixture-Ceiling-Cable-Kit-0.5m	73121020	100x100x5	0.40	6956321895266	1
542003021700	LEDPanelRc-S-B2 Suspension-Kit	73121049	315x315x25	0.13	6941408821665	1
542003021800	LEDPanelRc-S-B2 Mounting-Springs	73209090	280x200x170	0.10	6941408821672	1
542098000800	LEDPanelRC-SI U19 EM-kit 1h	85044083	490x390x150	0.98	6941497702340	1
542098000900	LEDPanelRC-SI U19 EM-kit 3h	85044083	490x390x150	1.08	6941497702333	1
542098009700	LEDPanelRc Sq625-Frame-WH	94059900	715x88x721	1.84	6941497704054	1
542098017500	LEDPanelRc2 Sq625-Surface-Kit-WH	94059900	812x77x68	1.59	6941497720689	1
542098030700	Junction-Box-WH	85369010	43x103.4x26	0.06	6941408868684	1

5 YEARS WARRANTY



Technical Specifications	
Lifetime (L70)	50,000 h
Lifetime (L80)	30,000 h
On-/Off-cycles	100,000
Colour consistency (SDCM)	4
Dimmability	On-Off
Finishing	White RAL9003
Colour rendering index (CRI)	> 80
Degree of protection (IP)	IP20
Impact strength	IK03
Protection class	II
Risk group (EN 62471)	RG0
With control gear	Yes
Glow wire test	650°C
Power factor	≥ 0.9


Electrical Supply	
Frequency	50/60 Hz
Nominal voltage	220-240 V
DC input voltage	See catalogue appendix Connection Specifications
230V Cable length	0.3 m

Mechanical Properties	
Housing material	Aluminium
Optical material	Polystyrene (PS)
Cover material	Polystyrene (PS)


Ambient Conditions	
Operating temperature	-10-+45°C
Application temperature	+25°C
Storage environment	-25-+50°C

Dimensional Drawing (mm)

LEDPanelS-B3 Sq620-32W



LEDPanelS-B3 Driver



Photometric Data

