



Slim Panel EcoMax G4

- Suitable for recessed and suspended applications
- Recessed ceiling frame and surface module kit available as accessory



Specifications

Item Code	Item Description	Equivalent to (W)	Power (W)	Lumen	Efficacy (lm/W)	UGR	CCT (K)	Beam angle	Weight (kg/pc)
On-Off									
542003100100	LEDPanelS-E4 Re295-32W-830	TL 2x36W	32	4000	125	≤ 22	3000	115°	1.43

Accessories

Surface Mounting Frame Recessed Mounting Frame

 <p>542098017700 LEDPanelRc2 Re300-Surface-Kit-WH</p>	 <p>542098009800 LEDPanelRc Re300-Frame-WH</p>	 <p>542098033000 LEDPanelRc-S-B2 Re298 Mounting-Springs</p>	 <p>542003021700 LEDPanelRc-S-B2 Suspension-Kit</p>	 <p>542098000800 LEDPanelRC-SI U19 EM-kit 1h</p>	 <p>542098000900 LEDPanelRC-SI U19 EM-kit 3h</p>
 <p>542098030700 Junction-Box-WH</p>	 <p>140060852 LEDFixture-Ceiling-Cable-Kit-0.5m</p>				

Packaging Information

Item			Box			
Item Code	Item Description	EU HS Code	Dimensions (mm) (LxWxH)	Gross Weight (kg)	EAN	pc/box
542003100100	LEDPanelS-E4 Re295-32W-830	94051190	1253x40x305	2.02	6941497771605	1
140060852	LEDFixture-Ceiling-Cable-Kit-0.5m	73121020	100x100x5	0.40	6956321895266	1
542003021700	LEDPanelRc-S-B2 Suspension-Kit	73121049	315x315x25	0.13	6941408821665	1
542098000800	LEDPanelRC-SI U19 EM-kit 1h	85044083	490x390x150	0.98	6941497702340	1
542098000900	LEDPanelRC-SI U19 EM-kit 3h	85044083	490x390x150	1.08	6941497702333	1
542098009800	LEDPanelRc Re300-Frame-WH	94059900	388x90x1290	1.93	6941497704047	1
542098017700	LEDPanelRc2 Re300-Surface-Kit-WH	94059900	1394x77x68	1.95	6941497720672	1
542098030700	Junction-Box-WH	85369010	43x103.4x26	0.06	6941408868684	1
542098033000	LEDPanelRc-S-B2 Re298 Mounting-Springs	73209090	280x200x170	3.65	6941497740151	1

Technical Specifications

Lifetime (L70)	60,000 h
Lifetime (L80)	50,000 h
On-/Off-cycles	100,000
Colour consistency (SDCM)	3
Dimmability	On-Off
Finishing	White RAL9003
Colour rendering index (CRI)	> 80
Degree of protection (IP)	IP20
Impact strength	IK03
Protection class	II
Risk group (EN 62471)	RG0
With control gear	Yes
Glow wire test	650°C
Power factor	≥ 0.9

Electrical Supply

Frequency	50/60 Hz
Nominal voltage	220-240 V
DC input voltage	See catalogue appendix Connection Specifications
230V Cable length	1 m

5 YEARS WARRANTY



Mechanical Properties


Housing material	Aluminum
Optical material	Polystyrene (PS)
Cover material	Polystyrene (PS)

Ambient Conditions


Operating temperature	-10-+45°C
Application temperature	+25°C
Storage environment	-25-+50°C

Dimensional Drawing (mm)


LEDPanelS-E4 Re295-32W



LEDPanelS-E4
Driver On/Off



LEDPanelS-E4
Driver DALI



Photometric Data

