



- Compact BLE to DALI converter for use in OPPLE Smart Lighting System
- Integrate any brand of DALI luminaire into the OPPLE Smart Lighting System
- Control of up to 64 DALI luminaires with Smart Switch or Smart App (DALI Broadcast commands, including Tunable White control of DALI DT8 luminaires)
- Compatible with OPPLE BLE2 Smart Sensors & OPPLE BLE2 Smart Switch
- Very easy to set up with the OPPLE Smart Lighting App, or Smart Connect Box through the web user interface
- Including built-in energy meter, to read out in the app or web user interface
- Complete wireless communication via future-proof, standardized Bluetooth[®] Low Energy (BLE) SIG Mesh protocol

Specifications

Material housing


Item CodeItem Description821017003200LEDSmart-BLE2-DALI-Converter


PC

Technical Specifications		Electrical Supply	
IP-class	IP20	Nominal voltage	220-240 V AC
Protection	II	Frequency	50 Hz
Finishing	White RAL9003	Connection cable	0.75mm ²
Communication	Opple Bluetooth® Low Energy SIG Mesh (BLE2)	Cable Length	12 cm
Dimming method	DALI Broadcast (DT8)		
Integrated DALI power supply	Yes		
		Ambient conditions	
Mechanical Properties		Application Temperature	+25°C

Operating Temperature

Dimensional	drawing	(mm)
Dimensional	urawing	





-20~+45°C

821017003200 - LEDSmart-BLE2-DALI-Converter

