



Panel Suspended Riga

- Stylish direct/indirect suspended LED panel
- Clean minimalistic design
- Low Glare UGR19, suitable for office spaces
- Flexible due to 3000/3500/4000K CCT and Power Switch
- DALI2 and Smart Lighting (BLE2) versions available
- DALI2 driver compatible with 230V push dimming



Specifications

Item Code	Item Description	Equivalent to (W)	Power (W)	Lumen	Efficacy (lm/W)	CCT (K)	Weight (kg/pc)
DALI2							
542004095200	LED Riga-P Re295-34/40W-DALI-830/840	TL 4x18W	34/40	4420/5200	130	3000/3500/4000	3.60
Smart							
542004095300	LED Riga-P Re295-34/40W-BLE2-830/840	TL 4x18W	34/40	4420/5200	130	3000/3500/4000	3.50

All codes include the required suspension kit. Suspension length 1.75m.
Available on request with Wieland GST18 or WAGO WINSTA connector, or Euro/Schuko plug.

Technical Specifications		Electrical Supply	
Lifetime (L70)	70,000 h	Frequency	50/60 Hz
Lifetime (L80)	50,000 h	Nominal voltage	220-240 V
On-/Off-cycles	100,000	DC input voltage	See catalogue appendix
Colour consistency (SDCM)	4	Connection	Specifications
Dimmability	DALI2 / BLE2	Mechanical Properties	
Beam angle	115° up (30%) + 90° down (70%)	Housing material	Aluminum
Finishing	White RAL9003	Optical material	PMMA
Colour rendering index (CRI)	> 80	Cover material	PMMA
UGR	≤ 19	Ambient Conditions	
Degree of protection (IP)	IP20	Operating temperature	-10-+35°C
Impact strength	IK02	Application temperature	+25°C
Protection class	II	Storage environment	-25-+50°C
Risk group (EN 62471)	RG0		
With control gear	Yes		
Glow wire test	650°C		
Power factor	≥ 0.9		

5 YEARS WARRANTY



Dimensional Drawing (mm)

LEDRiga-P

