



- Waterproof housing for use with LED TL tubes (tubes excluded), perfect in combination with the OPPLE LED T8 Tubes
- Flexible wiring options on side and backside
- Future-proof solution due to serviceability and upgradability of lamps
- Equipped with 3x1.5mm² throughwiring



Specifications


Item Code	Item Description	Weight (kg/pc)
Housing (excluding light source)		
531001001900	LEDWaterproof-CLA Housing L600-T8-1x	0.37
531001002000	LEDWaterproof-CLA Housing L600-T8-2x	0.53
531001002100	LEDWaterproof-CLA Housing L1200-T8-1x	0.67
531001002200	LEDWaterproof-CLA Housing L1200-T8-2x	0.89
531001002300	LEDWaterproof-CLA Housing L1500-T8-1x	0.89
531001002400	LEDWaterproof-CLA Housing L1500-T8-2x	1.13

Technical Specifications		Electrical Supply	
Beam angle	120°	Frequency	50/60 Hz
Finishing	Grey RAL 7035	Nominal voltage	220-240 V
Degree of protection (IP)	IP65	DC input voltage	No
Impact strength	IK08	Mechanical Properties	
Power factor	≥ 0.9	Material housing	Polycarbonate
Input wire diameter	1mm ² - 2.5mm ²	UV resistant	Yes
Internal wiring (mm ²)	3x2.5	Optical material	Polycarbonate
Max. input cable diameter (mm)	7-11.5 mm	Mounting clips	Stainless steel




Dimensional Drawing (mm)


LEDWaterproof-CLA Housing L600-T8-1x




LEDWaterproof-CLA Housing L600-T8-2x




LEDWaterproof-CLA Housing L1200-T8-1x




LEDWaterproof-CLA Housing L1200-T8-2x



LEDWaterproof-CLA Housing L1500-T8-1x



LEDWaterproof-CLA Housing L1500-T8-2x



Installation Possibilities

