



## Waterproof Classic Housing

- Waterproof housing for use with LED TL tubes (tubes excluded)
- Flexible wiring options on side and backside
- Future-proof solution due to serviceability and upgradability of lamps
- Equipped with 3x1.5mm<sup>2</sup> throughwiring
- Perfect in combination with the OPple LED T8 Tubes

IK08

IP65

## Specifications

Item Code	Item Description	Net Weight (kg/pc)
<b>Housing</b>		
531001001900	LEDWaterproof-CLA Housing L600-T8-1x	0.37
531001002000	LEDWaterproof-CLA Housing L600-T8-2x	0.53
531001002100	LEDWaterproof-CLA Housing L1200-T8-1x	0.665
531001002200	LEDWaterproof-CLA Housing L1200-T8-2x	0.89
531001002300	LEDWaterproof-CLA Housing L1500-T8-1x	0.89
531001002400	LEDWaterproof-CLA Housing L1500-T8-2x	1.13


Technical Specifications	
Beam angle	120°
Finishing	Grey RAL 7035
RAL-Number	7035
Ingress Protection (IP)	IP65
Impact strength (IK)	IK08
Input wire Ø (mm)	1mm <sup>2</sup> - 2.5mm <sup>2</sup>
Internal wiring (mm <sup>2</sup> )	3x1.5 mm <sup>2</sup>
Input cable Ø (mm)	7 - 11.5 mm

Electrical Supply	
Nominal voltage	220 - 240 V
DC input voltage	No

Mechanical Properties	
Housing material	Polycarbonate
Optical material	Polycarbonate
Mounting clips	Stainless steel



## Dimensional Drawing (mm)



Type	A	B	C
L600 1X	666	58	60
L600 2X	666	58	99
L1200 1X	1276	58	60
L1200 2X	1276	58	99
L1500 1X	1576	58	60
L1500 2X	1576	58	99

## Installation Possibilities

