



T8 Tube EcoMax

- Single-ended full IEC compliant LED Tube with patented driver
- 75% output/efficacy of T8 Tube Performer G2 with 130 lm/W
- Retrofit existing T8 lamps with EM ballast installations ONLY!
- No warm-up time, 100% light instantly when switched on
- Full glass body

IP20

CRI80

SAFE AND EASY INSTALLATION: ONLY USE WITH LED DUMMY STARTER.
Tubes are NOT suitable for serial installation.

Specifications

Item Code	Item Description	Equivalent to (W)	Power (W)	[Luminous flux]	Efficacy (lm/W)	CCT (K)	Weight (pc/kg)
On-Off							
802003022000	LEDTubeT8-EMB-E L1500-17W-865	TL 1x58W	17	2200	130	6500	0.26

Packaging information

Item			Box			
Item Code	Item Description	EU HS Code	Dimensions (mm) (LxWxH)	Gross Weight (kg)	EAN	pc/box
802003022000	LEDTubeT8-EMB-E L1500-17W-865	85395200	1555x26x26	0.42	6931783046821	1
802003022000	LEDTubeT8-EMB-E L1500-17W-865	85395200	1579x149x148	7.40	6931783049440	25

Technical Specifications

Lifetime (L70)	50,000 h
On-/Off-cycles	100,000
Dimmability	On-Off
Beam angle	220 °
Colour rendering index (CRI)	> 80
Fitting	G13

Electrical Supply


Frequency	50 - 60 Hz
Nominal voltage	220 - 240 V
DC input voltage	No

Mechanical Properties

Ambient Conditions

Operating temperature	-20 - 45 °C
Application temperature	25 °C
Storage environment	-25 ~ 50 °C

Dimensional Drawing (mm)



Installation Possibilities



Photometric Data

