

## LEDSmart-BLE2-Light-Wizard

Item  
Code

822008000200

Model


MT001XH - 1CB



0.2kg



Product Size: 74mm × 74mm × 23mm



## Product interfaces and control buttons


Top face  
control buttons



Control Ring

Type C interface  
for charging

Power ON/OFF  
Short Press



Daylight Sensor

Display Screen

Smart Scenes  
Short Press

Light Detection  
Short Press

Brightness  
Short Press  
and Rotate

CCT/Color  
Short Press  
and Rotate

ON/OFF  
Short Press



## Product Operation

1. Download the OPPLÉ Smart App from the App Store or Google Play, or login to the OPPLÉ web system.

2. Power on the Smart Light Wizard and add it to the OPPLÉ Smart App or Web system according to the Smart manual.



Smart manual

### 3. Control introduction

Button Icon	Button name	Button function
	Smart Scenes	<ol style="list-style-type: none"><li>1. Press the button to activate the scene control feature.</li><li>2. Select the scene via pressing the button or rotating the control ring. After 1 second, the scene will be activated.</li></ol>
	Brightness	<ol style="list-style-type: none"><li>1. Short press it to control brightness.</li><li>2. Rotate the ring to adjust the brightness, clockwise to brighten and anti-clockwise to dim.</li><li>3. The display will show +/- to help.</li></ol>
	ON/OFF	Short press it to turn on or off the lights.
	CCT/Color	<ol style="list-style-type: none"><li>1. Short press it to control CCT (When supported by the fixture).</li><li>2. Rotate the ring to adjust the CCT, clockwise to cooler and anti-clockwise to warmer.</li><li>3. The display will show +/- to help.</li></ol>
		<ol style="list-style-type: none"><li>1. Short press it again to control Colors (When supported by the fixture).</li><li>2. Rotate the ring to adjust the Colors, clockwise and anti-clockwise to change the light colors.</li><li>3. The display will show +/- to help.</li></ol>
	Light Detection	<ol style="list-style-type: none"><li>1. Short press it to start to measure the light in the room.</li><li>2. During the light measurement progress, the display screen will show the current illuminance, CCT and CRI value of the room.</li><li>3. After 60s the Light Wizard will turn off automatically.</li></ol>
	Reset	<ol style="list-style-type: none"><li>1. Press and hold these 2 buttons for more than 5 seconds until the screen turns off.</li><li>2. Release the button once the screen goes off. The screen will then display "Reset", indicating that the reset was successful.</li></ol>
	Wake Up	Tap to wake up the device and also set up automation.

## Important Installation Note:

1. If the Light Wizard does not power ON, please connect the Type C wire in the box to charge the unit.
2. For long-term storage, ensure the Light Wizard is powered off and charged at least once every two months. This will help preserve battery life.

Bluetooth Operating frequency: 2402-2480MHZ

Bluetooth Max.Transmission Power: <10dBm

This BLE accessory can only be used with OPPLE Smart luminaires



In case of damage to the wires, it has to be replaced only by the manufacturer distributor or an expert to avoid risks.

Zur Vermeidung von Risiken müssen defekte Leitungen ausschließlich vom Hersteller, Inverkehrbringer oder Fachmann ausgetauscht werden.



Correct Disposal of this product. This marking indicates that this product should not be disposed of with other household wastes throughout the EU.

Opplé Lighting B.V.  
Meerenakkerweg 1-07  
5652 AR Eindhoven  
The Netherlands  
service@opple.com  
www.opple.com

OPPLE Lighting Co., Ltd.  
Room 411, Building 1 No. 6111, Longdong Avenue, Pudong New District,  
Shanghai City 201201, P. R. China