



**LED Strip - IP20 - Chip On Board (COB)**

- Complete LED Strip portfolio
- Wide profile portfolio with different color options



**Specifications**

Item Code	Item Description	Efficacy (lm/W)	CCT (K)	LEDs per meter	Minimum cutting length	Power per meter	Lumen per meter	Net Weight (kg/pc)
<b>Chip On Board (COB)/IP20</b>								
806002000200	LEDStrip-P 12W-930-1000-COB-IP20	110	3000	280	42	12	1320	0.1

## Accessories



806098002000  
LEDStrip Profile-SF-15x15-AL



806098002200  
LEDStrip Profile-SF-17x7-AL



806098002500  
LEDStrip Profile-RC-15x15-AL



806098002600  
LEDStrip Profile-Corner-18x18-AL



806001009300  
LEDStrip Wire-Connector-SW-COB-IP20



806001009400  
LEDStrip Wire-Connector-SS-COB-IP20



806001009500  
LEDStrip Connector-SS-COB-IP20



806098004400  
LEDStrip L-Connector-SS-COB-IP20



820009008100  
LEDDriver 24V-120W



820009008200  
LEDDriver 24V-160W



820009008300  
LEDDriver 24V-240W



820002006200  
LEDDriver 24V-75W-DALI/10V/PWM




820002006300  
LEDDriver 24V-150W-DALI/10V/PWM



820002006400  
LEDDriver 24V-240W-DALI/10V/PWM

## Packaging information

Item			Box			
Item Code	Item Description	EU HS Code	Dimensions (mm) (LxWxH)	Gross Weight (kg/pc)	EAN	pc/box
806002000200	LEDStrip-P 12W-930-1000-COB-IP20	94054239	200x180x14	0.16	6931783054529	1
806098002000	LEDStrip Profile-SF-15x15-AL	94059900	2050x33x33	0.20	6931783054406	1
806098002100	LEDStrip Profile-SF-15x15-BL	94059900	2050x33x33	0.20	6931783054413	1
806098002200	LEDStrip Profile-SF-17x7-AL	94059900	2050x33x33	0.20	6931783054420	1
806098002300	LEDStrip Profile-SF-17x7-BL	94059900	2050x33x33	0.20	6931783054437	1
806098002500	LEDStrip Profile-RC-15x15-AL	94059900	2050x33x33	0.20	6931783054451	1
806098002600	LEDStrip Profile-Corner-18x18-AL	94059900	2050x33x33	0.20	6931783054468	1
806001009300	LEDStrip Wire-Connector-SW-COB-IP20	85444290	110x12x11	0.04	6931783054291	1
806001009400	LEDStrip Wire-Connector-SS-COB-IP20	85444290	18x12x11	0.04	6931783054321	1
806001009500	LEDStrip Connector-SS-COB-IP20	85444290	18x12x11	0.04	6931783054260	1
806098004400	LEDStrip L-Connector-SS-COB-IP20	85444290	21x21x21	0.04	6931783054352	1
820009008100	LEDDriver 24V-120W	85369010	298x50x38	0.23	6941491787398	1
820009008200	LEDDriver 24V-160W	85369010	298x50x38	0.28	6941491787404	1
820009008300	LEDDriver 24V-240W	85369010	335x51x38	0.28	6941491787411	1
820002006200	LEDDriver 24V-75W-DALI/10V/PWM	85369010	301x46x37	0.44	6941491788203	1
820002006300	LEDDriver 24V-150W-DALI/10V/PWM	85369010	301x46x37	0.44	6941491788210	1
820002006400	LEDDriver 24V-240W-DALI/10V/PWM	85369010	366x46x37	0.63	6941491788227	1
820002006500	LEDDriver 24V-75W-DALI-IP67	85369010	310x82x27	0.84	6941491788234	1
820002006600	LEDDriver 24V-150W-DALI-IP67	85369010	310x82x27	0.83	6941491788241	1
820002006700	LEDDriver 24V-240W-DALI-IP67	85369010	290x85x31	1.08	6941491788258	1
820003003900	LEDDriver 24V-75W-10V/PWM-IP67	85369010	310x82x27	0.81	6941491788265	1
820003004000	LEDDriver 24V-150W-10V/PWM-IP67	85369010	310x82x27	0.85	6941491788272	1
820003004100	LEDDriver 24V-240W-10V/PWM-IP67	85369010	290x85x31	1.08	6941491788289	1



### Technical Specifications

Lifetime (L70)	50,000
Dimmability	DALI2 / 1-10V / PWM
Colour rendering index (CRI)	> 90
Ingress Protection (IP)	IP20
Risk group (EN 62471)	RG0
With control gear	False

### Electrical Supply

Frequency	50 - 60
Nominal voltage	220 - 240

### Mechanical Properties

Length	5000
--------	------

### Ambient Conditions

Operating temperature	-10 - 45 °C
Application temperature	25 °C
Storage environment	-25 - 50 °C

## Dimensional Drawing (mm)

