



Floodlight Olympus G2

- Powerful professional floodlighting solution for Sports and Area lighting
- All-in-one LED driver with flexible mounting methods and 220-400VAC power input
- Standard compatible with DALI2 / 1-10V / DMX dimming
- Robust design: full IP66 and IK08 protection, including safety cable
- Equipped with breather to prevent condensation



Specifications

Item Code	Item Description	Equivalent to (W)	Power (W)	Lumen Efficacy (lm/W)	CCT (K)	Beam angle	Net Weight (kg/pc)
Driver possibilities							
720001010000	FloodOly-P2 Driver-600W-DA/10V/DMX		600				5.52

Packaging information

Item			Box			
Item Code	Item Description	EU HS Code	Dimensions (mm) (LxWxH)	Gross Weight (kg/pc)	EAN	pc/box
720001010000	FloodOly-P2 Driver-600W-DA/10V/DMX	85369010	515x230x210	6.80	6941491785677	1

Technical Specifications

Dimmability	DALI2 / 1-10V / DMX
Ingress Protection (IP)	IP66
Impact strength (IK)	IK08
Protection class	I
With control gear	True
Power factor	≥ 0.95

Electrical Supply

Nominal voltage	200 - 528 V
-----------------	-------------

Mechanical Properties

Housing material	Aluminium
------------------	-----------

Ambient Conditions

Application temperature	25 °C
-------------------------	-------



Dimensional Drawing (mm)

