



## LED Strip - IP67

- Complete LED Strip portfolio
- LED Strip power range from 4.8 W/m to 14.4 W/m, with minimum 120 Leds per meter
- Multiple driver options available including on/off, DALI, 1-10V, PWM
- Wide profile portfolio with different color options
- Complete set of strip connectors for IP67 strip



## Specifications

Item Code	Item Description	Lumen (lm/m)	LEDs per meter	Power (W/m)	Minimum cutting length	CCT (K)	Net Weight (kg/pc)
<b>IP67</b>							
806001007300	LEDStrip-E 4.8W-927-600-IP67	600	120	4.8	50	2700	0.25
806001007400	LEDStrip-E 4.8W-930-600-IP67	600	120	4.8	50	3000	0.25
806001007500	LEDStrip-E 4.8W-940-600-IP67	600	120	4.8	50	4000	0.25
806001007900	LEDStrip-E 9.6W-927-1200-IP67	1200	140	9.6	50	2700	0.25
806001008000	LEDStrip-E 9.6W-930-1200-IP67	1200	140	9.6	50	3000	0.25
806001008100	LEDStrip-E 9.6W-940-1200-IP67	1200	140	9.6	50	4000	0.25
806001008700	LEDStrip-E 14.4W-927-1800-IP67	1730	140	14.4	42	2700	0.25
806001008800	LEDStrip-E 14.4W-930-1800-IP67	1730	140	14.4	42	3000	0.25
806001008900	LEDStrip-E 14.4W-940-1800-IP67	1730	140	14.4	42	4000	0.25

## Accessories

					
806098001800 LEDStrip Profile-SF-10x10-AL	806098002000 LEDStrip Profile-SF-15x15-AL	806098002200 LEDStrip Profile-SF-17x7-AL	806098002400 LEDStrip Profile-RC-10x10-AL	806098002500 LEDStrip Profile-RC-15x15-AL	806098002600 LEDStrip Profile-Corner-18x18-AL
806098001900 LEDStrip Profile-SF-10x10-BL	806098002100 LEDStrip Profile-SF-15x15-BL	806098002300 LEDStrip Profile-SF-17x7-BL			
					
806098004600 LEDStrip Silicone-Kit-IP67	806098004700 LEDStrip Mounting-Kit-10-IP67	820002006500 LEDDriver 24V-75W-DALI-IP67	820002006600 LEDDriver 24V-150W-DALI-IP67	820002006700 LEDDriver 24V-240W-DALI-IP67	820003003900 LEDDriver 24V-75W-10V/PWM-IP67
					
820003004000 LEDDriver 24V-150W-10V/PWM-IP67	820003004100 LEDDriver 24V-240W-10V/PWM-IP67				

It is recommended to use a power supply between 120% and 150% of the total power needed for the LED Strip. The 10mm x 10mm profiles can only be used for the 4.8W and 9.6W LED Strips.

All profiles have a length of 2m and come with a polycarbonate cover as well as 4 end caps - 2 end caps suitable for wirethrough, and 2 standard end caps.

Technical Specifications		Electrical Supply	
Lifetime (L70)	50,000 h	Frequency	50 - 60 Hz
Dimmability	DALI2 / 1-10V / PWM	Nominal voltage	220 - 240 V
Colour rendering index (CRI)	> 90	Mechanical Properties	
Ingress Protection (IP)	IP67	Length (mm)	5000
Risk group (EN 62471)	RG0	Ambient Conditions	
With control gear	No	Operating temperature	-10 - 45°C
		Application temperature	25°C
		Storage environment	-25 - 50°C



## Dimensional Drawing (mm)

