



**LED Strip - IP67 - Tunable White**

- Complete LED Strip portfolio
- Multiple driver options available
- Wide profile portfolio with different color options
- Complete set of strip connectors for IP67 strip



**Specifications**

Item Code	Item Description	Lumen (lm/m)	LEDs per meter	Power (W/m)	Minimum cutting length	CCT (K)	Net Weight (kg/pc)
<b>Smart/IP67</b>							
806001008600	LEDStrip-P 12W-1000-TW-IP67	1440	140	12	100	2700 - 6500	0.25

**Accessories**

					
806098002000 LEDStrip Profile-SF-15x15-AL	806098002200 LEDStrip Profile-SF-17x7-AL	806098002500 LEDStrip Profile-RC-15x15-AL	806098002600 LEDStrip Profile-Corner-18x18-AL	806098004600 LEDStrip Silicone-Kit-IP67	806098004700 LEDStrip Mounting-Kit-10-IP67
806098002100 LEDStrip Profile-SF-15x15-BL	806098002300 LEDStrip Profile-SF-17x7-BL				
					
820004013700 LEDDriver 24V-200W-BLE2-TW	826001000300 LEDDriver 24V-80W-BLE2-TW				

It is recommended to use a power supply between 120% and 150% of the total power needed for the LED Strip. Extra measures are required for Tunable White drivers to obtain an IP rating for outdoor applications.

### Technical Specifications

Lifetime (L70)	50,000 h
Dimmability	BLE2
Colour rendering index (CRI)	> 90
Ingress Protection (IP)	IP67
Risk group (EN 62471)	RG0
With control gear	No

### Electrical Supply

Frequency	50 - 60 Hz
Nominal voltage	220 - 240 V

### Mechanical Properties


Length (mm)	5000
-------------	------

### Ambient Conditions

Operating temperature	-10 - 45°C
Application temperature	25°C
Storage environment	-25 - 50°C



## Dimensional Drawing (mm)



IP20 Driver	A	B	C
80W	230	45	25
200W	311	48	26



Strip IP67	A	B	C	D	E
12W	5000	300	9	4,5	100

