



Panel Vienna

- Design low glare LED panel
- Comfortable lighting for study and work environment (UGR < 16)
- Standard equipped with CCT-switch and CRI90
- Also available as Tunable White version
- System efficacy up to 125 lm/W
- Compatible with Slim Panel surface mounting kit accessory
- Available in DALI2 and Smart (BLE2) versions
- DALI2 driver compatible with 230V push dimming



Specifications

Item Code	Item Description	Equivalent to (W)	Power (W)	Lumen	Efficacy (lm/W)	CCT (K)	Net Weight (kg/pc)
On-Off							
542003173500	LEDVienna-P Re295-32W-930/940-U16	TL 2x36W	32	4000	125	3K/4K	1.7
542003173600	LEDVienna-P Sq595-32W-930/940-U16	TL 4x18W	32	4000	125	3K/4K	1.7
DALI2							
542003173900	LEDVienna-P Re295-32W-DALI-930/940-U16	TL 2x36W	32	4000	125	3K/4K	1.7
542003174000	LEDVienna-P Sq595-32W-DALI-930/940-U16	TL 4x18W	32	4000	125	3K/4K	1.7
Tunable White/DALI2							
542003174400	LEDVienna-P Sq595-32W-DALI-TW-U16	TL 4x18W	32	4000	125	2.7K-6.5K	1.8
Smart							
542003173700	LEDVienna-P Re295-32W-BLE2-930/940-U16	TL 2x36W	32	4000	125	3K/4K	1.7
542003173800	LEDVienna-P Sq595-32W-BLE2-930/940-U16	TL 4x18W	32	4000	125	3K/4K	1.7
Tunable White/Smart							
542003174200	LEDVienna-P Sq595-32W-BLE2-TW-U16	TL 4x18W	32	4000	125	2.7K-6.5K	1.8

Available on request with Wieland GST18 or WAGO WINSTA connector, or Euro/Schuko plug. Emergency lighting available on request. BLE versions in surface mounting frames might lead to limited BLE signal strength.

Accessories



140060852
LEDFixture-Ceiling-Ca-
ble-Kit-0.5m

542098000800
LEDPanelRC-SI U19 EM-
kit 1h

542003021700
LEDPanelRc-S-B2 Suspen-
sion-Kit

542003021800
LEDPanelRc-S-B2 Moun-
ting-Springs

542098009600
LEDPanelRc Sq600-Frame-
WH

542098009800
LEDPanelRc Re300-Frame-
WH

542098017600
LEDPanelRc2 Sq600-Sur-
face-Kit-WH

542098017700
LEDPanelRc2 Re300-Sur-
face-Kit-WH

542098030700
Junction-Box-WH

542098033000
LEDPanelRc-S-B2 Re298
Mounting-Springs

Technical Specifications

Lifetime (L70)	100,000 h
Lifetime (L80)	70,000 h
On-/Off-cycles	100,000
Colour consistency (SDCM)	4
Dimmability	On-Off / DALI2 / BLE2
Beam angle	90°
Finishing	White RAL9003
RAL-Number	○ 9003
Colour rendering index (CRI)	> 90
UGR	≤ 16
Ingress Protection (IP)	IP20
Impact strength (IK)	IK03
Protection class	II
Risk group (EN 62471)	RG0
With control gear	Yes
Glow wire test	650°C
Driver failure rate (at 5,000 hrs)	< 1%
Power factor	> 0.9

Electrical connection

Frequency	50 - 60 Hz
Nominal voltage	220 - 240 V
DC input voltage	See catalogue appendix Connection Specifications

Mechanical Properties

Housing material	Aluminium
Optical material	Polycarbonate

Ambient Conditions

Operating temperature	-10 - 45°C
Application temperature	25°C
Storage environment	-25 - 50°C



Dimensional Drawing (mm)

