



Waterproof Batten

- Cost effective IP65 Waterproof solution
- Slim and compact design
- 1m cable with IP65-connector
- Perfect light uniformity
- Supplied with stainless steel mounting clips, movable along the entire length of the fixture



Specifications

Item Code	Item Description	Equivalent to (W)	Power (W)	Lumen	Efficacy (lm/W)	CCT (K)	Net Weight (kg/pc)
On-Off							
531000022800	LEDWaterproof-Batten L06-18W-840	TL 1x36W	18	2000	110	4000	0.25
531000022900	LEDWaterproof-Batten L12-36W-840	TL 2x36W	36	4000	110	4000	0.28
531000023000	LEDWaterproof-Batten L15-50W-840	TL 2x58W	50	5500	110	4000	0.553

Technical Specifications	
Lifetime (L70)	30,000 h
On-/Off-cycles	60,000
Colour consistency (SDCM)	4
Dimmability	On-Off
Beam angle	120°
Finishing	Grey Pantone 419U
Colour rendering index (CRI)	> 80
Ingress Protection (IP)	IP65
Impact strength (IK)	IK06
Protection class	II
Risk group (EN 62471)	RG0
With control gear	Yes
Glow wire test	650°C
Driver failure rate (at 5,000 hrs)	< 1%
Power factor	> 0.9


Electrical Supply	
Frequency	50 - 60 Hz
Nominal voltage	220 - 240 V
DC input voltage	No

Mechanical Properties	
Housing material	Polycarbonate
Optical material	Polycarbonate
Mounting clips	Stainless steel

Ambient Conditions	
Operating temperature	-20 - 40°C
Application temperature	25°C
Storage environment	-20 - 40°C



Dimensional Drawing (mm)



Installation Possibilities

