



- Elegant combination of ceiling fan and luminaire
- High-quality, ultra-quiet motor
- Automatically retractable fan blades
- Dimmable with multi-CCT via remote
- Six adjustable fan speeds
- Reversible airflow for year-round use



Specifications

Item Code	Item Description	Equivalent to (W)	Power (W)	Lumen	Efficacy (lm/W)	CCT (K)	Beam angle	Volume flow	Sound level	Net Weight (kg/pc)
On-Off										

525006003800	LEDFanlight-E Rd510-45+40W-830/840/857		85	5000	111	3K/4K/5.7K	120°	220	32 - 52	5.54
--------------	--	--	----	------	-----	------------	------	-----	---------	------

Packaging information

Item			Box			
Item Code	Item Description	EU HS Code	Dimensions (mm) (LxWxH)	Gross Weight (kg/pc)	EAN	pc/box
525006003800	LEDFanlight-E Rd510-45+40W-830/840/857	94051190	580x580x205	6.30	6941497793188	1



Technical Specifications	
Lifetime (L70)	50,000 h
Lifetime (L80)	30,000 h
On-/Off-cycles	100,000
Colour consistency (SDCM)	4
Dimmability	STEP
RAL-Number	9016
Colour rendering index (CRI)	> 80
Ingress Protection (IP)	IP20
Ingress protection front side (IP)	IP40
Impact strength (IK)	IK02
Protection class	I
Risk group (EN 62471)	RG0
With control gear	True
Glow wire test	650 °C
Driver failure rate (at 5,000 hrs)	≤ 0.05 %
Power factor	≥ 0.9

Electrical Supply	
Frequency	50 - 60 Hz
Nominal voltage	220 - 240 V

Mechanical Properties	
Housing material	Aluminium
Cover material	PMMA

Ambient Conditions	
Operating temperature	-10 - 45 °C
Application temperature	25 °C
Storage environment	-25 - 50 °C

Dimensional Drawing (mm)

