



Fanlight

- Elegant combination of ceiling fan and luminaire
- High-quality, ultra-quiet motor
- Automatically retractable fan blades
- Dimmable with multi-CCT via remote
- Six adjustable fan speeds
- Reversible airflow for year-round use



Specifications

Item Code	Item Description	Power (W)	Lumen	Efficacy (lm/W)	CCT (K)	Beam angle	Sound level (dB)	Volume flow (m3/min)	Net Weight (kg/pc)
On-Off									
525006003700	LEDFanlight-E Rd434-27+36W-830/840/857	63	3000	111	3K/4K/5.7K	120°	32 - 52	190	4.3
525006003800	LEDFanlight-E Rd510-45+40W-830/840/857	85	5000	111	3K/4K/5.7K	120°	32 - 52	220	5.54

Technical Specifications	
Lifetime (L70)	50,000 h
Lifetime (L80)	30,000 h
On-/Off-cycles	100,000
Colour consistency (SDCM)	4
Dimmability	STEP
RAL-Number	9016
Colour rendering index (CRI)	> 80
Ingress Protection (IP)	IP20
Ingress protection front side (IP)	IP40
Impact strength (IK)	IK02
Protection class	I
Risk group (EN 62471)	RG0
With control gear	Yes
Glow wire test	650°C
Driver failure rate (at 5,000 hrs)	< 0.05%
Power factor	> 0.9

Electrical Supply	
Frequency	50 - 60 Hz
Nominal voltage	220 - 240 V

Mechanical Properties	
Housing material	Aluminium
Cover material	PMMA

Ambient Conditions	
Operating temperature	-10 ~ 45°C
Application temperature	25°C
Storage environment	-25 ~ 50°C



Dimensional Drawing (mm)

