



## Suspended Halo

- Stylish, slim round luminaire for suspended and surface mounted applications
- Three refined sizes: 400 mm, 600 mm, and 800 mm diameter



## Specifications

Item Code	Item Description	Equivalent to (W)	Power (W)	Lumen (lm)	Efficacy (lm/W)	Efficacy (lm/W)	CCT (K)	Sensor	Net Weight (kg/pc)
<b>DALI2</b>									
520036048100	LEDHalo-P Rd600-DALI-40W-830/840-D-U19	TL 1x80W	40	5000		125	3K/4K	False	4.9

## Packaging information

Item			Box			
Item Code	Item Description	EU HS Code	Dimensions (mm) (LxWxH)	Gross Weight (kg/pc)	EAN	pc/box
520036048100	LEDHalo-P Rd600-DALI-40W-830/840-D-U19	94051190	640x640x120	5.15	6937209634351	1
542098001000	LEDTrunking DALI Power Supply	85044083	198x54x39	0.24	6945730496614	1
520098005800	LEDHalo-P-Uplight-M	94059900	420x420x40	1.13	6937209634719	1

Technical Specifications	
Lifetime (L70)	100,000 h
Lifetime (L80)	70,000 h
On-/Off-cycles	100,000
Colour consistency (SDCM)	4
Dimmability	DALI2
Sensor type	No sensor
Sensor technology	-
Beam angle	90°
Finishing	White RAL9003
Colour rendering index (CRI)	> 80
UGR	19
Ingress protection front side (IP)	IP20
Impact strength (IK)	IK03
Protection class	I
Risk group (EN 62471)	RG0
With control gear	True
Glow wire test	650 °C
Driver failure rate (at 5,000 hrs)	≤ 1 %
Power factor	≥ 0.9

Electrical Supply	
Frequency	50 - 60 Hz
Nominal voltage	180 - 280 V
DC input voltage	See catalogue appendix Connection Specifications

Mechanical Properties	
Housing material	Aluminium
Cover material	PMMA

Ambient Conditions	
Operating temperature	-10 ~ 45 °C
Application temperature	25 °C
Storage environment	-25 ~ 50 °C



## Dimensional Drawing (mm)

