

# Trunking P2

- Trunking system with modular freedom: Free-to-place LED modules and extensive layout accessories
- High Performance: Powerful output up to 24,690 lm with tailored beam optics
- Fast Installation: Versatile 1,5m to 4,5m trunks to fit any project size
- Industrial Grade: Durable IP54 rated options for demanding environments
- Future-Proof Efficiency: Ultra-high efficacy up to 208 lm/W, with smart savings via DALI-2 dimming and integrated sensors

## Packaging information

| Item | | | Box | | | |
|---|---|---|---|---|---|---|
| Item Code | Item Description | EU HS Code | Dimensions (mm) (LxWxH) | Gross Weight (kg/pc) | EAN | pc/box |
| 552001000400 | Trunk-P2 Trunk 13-Wire L30-WH | 94059900 | 3570x240x165 | 6.54 | 6937209647436 | 1 |

| Technical Specifications | | | |
|---|---|---|---|
| Protection class according to IEC 61140 | I | Length | 2996 mm |
| Colour | White | Material | Steel |
| Width | 67 mm | Cross section wiring cores | 2.5 mm² |
| Model | Double module length | Degree of protection (IP) | IP20 |
| Height | 45 mm | Storage environment | -30~ 70 °C |
| With wiring | Yes | Operating temperature | -20~ 50 °C |
| Number of cores wiring | 13 | Finishing | White RAL9003 |

## Dimensional Drawing (mm)




| Type | A | B | C |
|---|---|---|---|
| L15 DF | 1437 | 67 | 47 |
| L15 | 1437 | 67 | 25 |
| L22 | 2155 | 67 | 25 |




| Type | A | B | C | D |
|---|---|---|---|---|
| L15 | 1558 | 1437 | 68 | 46 |
| L30 | 2995 | 2874 | 68 | 46 |
| L45 | 4432 | 4311 | 68 | 46 |