

Trunking P2

- Trunking system with modular freedom: Free-to-place LED modules and extensive layout accessories
- High Performance: Powerful output up to 24,690 lm with tailored beam optics
- Fast Installation: Versatile 1,5m to 4,5m trunks to fit any project size
- Industrial Grade: Durable IP54 rated options for demanding environments
- Future-Proof Efficiency: Ultra-high efficacy up to 208 lm/W, with smart savings via DALI-2 dimming and integrated sensors

Packaging information

Item			Box			
Item Code	Item Description	EU HS Code	Dimensions (mm) (LxWxH)	Gross Weight (kg/pc)	EAN	pc/box
552001001700	Trunk-P2 Trunk-Ending 13-Wire L45-WH	94059900	4384x240x165	9.12	6937209647566	1

Technical Specifications			
Protection class according to IEC 61140	I	Length	4311 mm
Colour	White	Material	Steel
Width	67 mm	Cross section wiring cores	2.5 mm²
Model	Double module length	Degree of protection (IP)	IP20
Height	45 mm	Storage environment	-30~ 70 °C
With wiring	Yes	Operating temperature	-20~ 50 °C
Number of cores wiring	13	Finishing	White RAL9003

Dimensional Drawing (mm)



Type	A	B	C
L15 DF	1437	67	47
L15	1437	67	25
L22	2155	67	25



Type	A	B	C	D
L15	1558	1437	68	46
L30	2995	2874	68	46
L45	4432	4311	68	46