



## Linear Clio EcoMax

- Linear Clio EcoMax has a compact design, perfect for upgrading old tube fixtures in existing metal housings
- Luminaire with integrated CCT-switch for color selection (3000K/4000K)
- Driver with integrated Power Switch
- Easy to install with both magnetic and screw mounting options included
- DC compatibility makes it suitable for use with central emergency lighting systems



## Specifications

Item Code	Item Description	Equivalent to (W)	Power (W)	Lumen (lm)	CCT (K)	Net Weight (kg/pc)
<b>On-Off/CCT-Switch</b>						
805012006800	LEDCLio-Lin-E L06-7/14W-830/840	TL 1x35W	7 - 14	1120 - 2240	3K/4K	0.13

## Packaging information

Item			Box			
Item Code	Item Description	EU HS Code	Dimensions (mm) (LxWxH)	Gross Weight (kg/pc)	EAN	pc/box
805012006800	LEDCLio-Lin-E L06-7/14W-830/840	94054239	600x40x36	0.18	6937209622853	1

### Technical Specifications

Lifetime (L70)	70,000 h
Lifetime (L80)	50,000 h
On-/Off-cycles	25,000
Dimmability	On-Off
Beam angle	145 °
Colour rendering index (CRI)	> 80
Ingress Protection (IP)	IP20
Protection class	II
With control gear	True


### Electrical Supply

Frequency	50 - 60 Hz
Nominal voltage	220 - 240 V
DC input voltage	See catalogue appendix Connection Specifications


### Mechanical Properties

### Ambient Conditions

Operating temperature	-25 - 45 °C
Application temperature	25 °C
Storage environment	-20 - 60 °C



## Dimensional Drawing (mm)



Type	A	B	C
L06	585	35	34
L12	1185	35	34
L15	1485	35	34

## Photometric Data

