



LED Strip - IP20 - Chip On Board (COB)

- Compleet assortiment LED Strips
- Breed profielportfolio met verschillende kleuropties



Specificaties

Artikelcode	Artikelomschrijving	Efficiëntie (lm/W)	CCT (K)	LEDs per meter	Minimale snijlengte	Vermogen per meter	Lumen per meter	Nettogewicht (kg/st)
Chip On Board (COB)/IP20								
806002000200	LEDStrip-P 12W-930-1000-COB-IP20	110	3000	280	42	12	1320	0.1

Accessoires



806098002000
LEDStrip Profile-SF-15x15-AL



806098002200
LEDStrip Profile-SF-17x7-AL



806098002500
LEDStrip Profile-RC-15x15-AL



806098002600
LEDStrip Profile-Corner-18x18-AL



806001009300
LEDStrip Wire-Connector-SW-COB-IP20



806001009400
LEDStrip Wire-Connector-SS-COB-IP20



806001009500
LEDStrip Connector-SS-COB-IP20



806098004400
LEDStrip L-Connector-SS-COB-IP20



820009008100
LEDDriver 24V-120W




820009008200
LEDDriver 24V-160W



820009008300
LEDDriver 24V-240W



820002006200
LEDDriver 24V-75W-DALI/10V/PWM




820002006300
LEDDriver 24V-150W-DALI/10V/PWM



820002006400
LEDDriver 24V-240W-DALI/10V/PWM

Artikel- en verpakkingsinformatie

Item			Doos			
Artikelcode	Artikelomschrijving	EU HS-code	Afmetingen (mm) (LxBxH)	Brutogewicht (kg/st)	EAN	st/doos
806002000200	LEDStrip-P 12W-930-1000-COB-IP20	94054239	200x180x14	0.16	6931783054529	1
806098002000	LEDStrip Profile-SF-15x15-AL	94059900	2050x33x33	0.20	6931783054406	1
806098002100	LEDStrip Profile-SF-15x15-BL	94059900	2050x33x33	0.20	6931783054413	1
806098002200	LEDStrip Profile-SF-17x7-AL	94059900	2050x33x33	0.20	6931783054420	1
806098002300	LEDStrip Profile-SF-17x7-BL	94059900	2050x33x33	0.20	6931783054437	1
806098002500	LEDStrip Profile-RC-15x15-AL	94059900	2050x33x33	0.20	6931783054451	1
806098002600	LEDStrip Profile-Corner-18x18-AL	94059900	2050x33x33	0.20	6931783054468	1
806001009300	LEDStrip Wire-Connector-SW-COB-IP20	85444290	110x12x11	0.04	6931783054291	1
806001009400	LEDStrip Wire-Connector-SS-COB-IP20	85444290	18x12x11	0.04	6931783054321	1
806001009500	LEDStrip Connector-SS-COB-IP20	85444290	18x12x11	0.04	6931783054260	1
806098004400	LEDStrip L-Connector-SS-COB-IP20	85444290	21x21x21	0.04	6931783054352	1
820009008100	LEDDriver 24V-120W	85369010	298x50x38	0.23	6941491787398	1
820009008200	LEDDriver 24V-160W	85369010	298x50x38	0.28	6941491787404	1
820009008300	LEDDriver 24V-240W	85369010	335x51x38	0.28	6941491787411	1
820002006200	LEDDriver 24V-75W-DALI/10V/PWM	85369010	301x46x37	0.44	6941491788203	1
820002006300	LEDDriver 24V-150W-DALI/10V/PWM	85369010	301x46x37	0.44	6941491788210	1
820002006400	LEDDriver 24V-240W-DALI/10V/PWM	85369010	366x46x37	0.63	6941491788227	1
820002006500	LEDDriver 24V-75W-DALI-IP67	85369010	310x82x27	0.84	6941491788234	1
820002006600	LEDDriver 24V-150W-DALI-IP67	85369010	310x82x27	0.83	6941491788241	1
820002006700	LEDDriver 24V-240W-DALI-IP67	85369010	290x85x31	1.08	6941491788258	1
820003003900	LEDDriver 24V-75W-10V/PWM-IP67	85369010	310x82x27	0.81	6941491788265	1
820003004000	LEDDriver 24V-150W-10V/PWM-IP67	85369010	310x82x27	0.85	6941491788272	1
820003004100	LEDDriver 24V-240W-10V/PWM-IP67	85369010	290x85x31	1.08	6941491788289	1



Technische specificaties	
Levensduur (L70)	50.000
Dimbaarheid	DALI2 / 1-10V / PWM
Kleurweergave index (CRI)	> 90
Beschermingsgraad (IP)	IP20
Risicogroep (EN 62471)	RG0
Voorschakelapparaat inbegrepen	Nee

Elektrische aansluiting	
Frequentie	50 - 60
Nominale spanning	220 - 240
Materiaal eigenschappen	
Lengte	5000
Toepassingscondities	
Bedrijfstemperatuur	-10 - 45 °C
Gebruikstemperatuur	25 °C
Opslagtemperatuur	-25 - 50 °C

Maatschets (mm)

Strip IP20	A	B	C	D	E
4,8W	5000	300	8	1,5	50
9,6W	5000	300	8	1,5	50
14,4W	5000	300	8	1,5	42
19,2W	5000	300	8	1,5	42

IP20	Driver		
Driver	A	B	C
75W	295	40	32
120W	260	45	32
150W	295	40	31
160W	260	45	32
240W	310	50	32