



## Lima G2

- Elegant linear luminaire with premium aluminium housing — available in Aluminium or Black finish
- Connection kit accessory to create continuous lines available
- Modular connection options with L-, T-, X- and I-connectors — ideal for continuous lines or custom layout designs
- UGR < 19 in all versions for comfortable visual comfort
- Direct versions and Direct/Indirect versions with uplight available
- Suspension kit including transparent cable available as accessory
- Available as DALI2 and Smart Lighting solution (BLE2)



## Specifications

Item Code	Item Description	Equivalent to (W)	Power (W)	Lumen	Efficacy (lm/W)	CCT (K)	Finishing	Net Weight (kg/pc)
<b>DALI2</b>								
529000318300	LEDLima-P2 L12-28W-DALI-830/840-U19-BL	TL 1x54W	28	3360	120	3K/4K	■	3
529000318500	LEDLima-P2 L12-28W-DALI-830/840-U19-AL	TL 1x54W	28	3640	130	3K/4K	■	3
529000318700	LEDLima-P2 L15-33W-DALI-830/840-U19-BL	TL 1x54W	33	3960	120	3K/4K	■	3.7
529000318900	LEDLima-P2 L15-33W-DALI-830/840-U19-AL	TL 1x54W	33	4290	130	3K/4K	■	3.7
529000319100	LEDLima-P2 L12-20W-DALI-830/840-D-U19-BL	TL 1x35W	20	2000	100	3K/4K	■	2.9
529000319300	LEDLima-P2 L12-20W-DALI-830/840-D-U19-AL	TL 1x35W	20	2300	115	3K/4K	■	2.9
529000319500	LEDLima-P2 L15-23W-DALI-830/840-D-U19-BL	TL 1x35W	23	2300	100	3K/4K	■	3.6
529000319700	LEDLima-P2 L15-23W-DALI-830/840-D-U19-AL	TL 1x35W	23	2645	115	3K/4K	■	3.6
<b>Smart</b>								
529000318400	LEDLima-P2 L12-28W-BLE2-830/840-U19-BL	TL 1x54W	28	3360	120	3K/4K	■	3
529000318600	LEDLima-P2 L12-28W-BLE2-830/840-U19-AL	TL 1x54W	28	3640	130	3K/4K	■	3
529000318800	LEDLima-P2 L15-33W-BLE2-830/840-U19-BL	TL 1x54W	33	3960	120	3K/4K	■	3.7
529000319000	LEDLima-P2 L15-33W-BLE2-830/840-U19-AL	TL 1x54W	33	4290	130	3K/4K	■	3.7
529000319200	LEDLima-P2 L12-20W-BLE2-830/840-D-U19-BL	TL 1x35W	20	2000	100	3K/4K	■	2.9
529000319400	LEDLima-P2 L12-20W-BLE2-830/840-D-U19-AL	TL 1x35W	20	2300	115	3K/4K	■	2.9
529000319600	LEDLima-P2 L15-23W-BLE2-830/840-D-U19-BL	TL 1x35W	23	2300	100	3K/4K	■	3.6
529000319800	LEDLima-P2 L15-23W-BLE2-830/840-D-U19-AL	TL 1x35W	23	2645	115	3K/4K	■	3.6

## Accessories

					
529098052800 Lima I-connection-G2	529098052900 Lima L-connection-G2-BL	529098053000 Lima T-connection-G2-BL	529098053100 Lima X-connection-G2-BL	529098053500 LEDLima-P2-Canopy-BL	529098053700 LEDLima-P2-Lens-12m
529098052800 Lima I-connection-G2	529098053200 Lima L-connection-G2-AL	529098053300 Lima T-connection-G2-AL	529098053400 Lima X-connection-G2-AL	529098053600 LEDLima-P2-Canopy-AL	

Technical Specifications	
Lifetime (L70)	100,000 h
Lifetime (L80)	70,000 h
On-/Off-cycles	100,000
Dimmability	DALI2 / BLE2
Beam angle	90°
Finishing	Black RAL 9004 / Aluminum
Colour rendering index (CRI)	> 80
UGR	19
Impact strength (IK)	IK03
Protection class	I
Risk group (EN 62471)	RG0
With control gear	Yes
Glow wire test	650°C
Driver failure rate (at 5,000 hrs)	< 1%
Power factor	> 0.9


Electrical Supply	
Frequency	50 - 60 Hz
Nominal voltage	220 - 240 V
DC input voltage	See catalogue appendix Connection Specifications

Mechanical Properties	
Housing material	Aluminium

Ambient Conditions	
Operating temperature	-10 - 45°C
Application temperature	25°C
Storage environment	-25 - 50°C



## Dimensional Drawing (mm)



Type	A	B	C
L12	1202	85	70
L15	1502	85	70