



Waterproof Performer G5

- Powerful range of waterproof luminaires in specific “sealed for life” design
- High efficacy of 170 lm/w
- Available as Smart Lighting solution (BLE2) and DALI2
- Smart Lighting solution (BLE2) and DALI2 versions with Tunable White (3000K - 5700K) available
- Flexible due to 4000K/5700K CCT and Power Switch
- Quick installation thanks to its screwless endcap
- Supplied with vandal-proof stainless steel ceiling and suspension clips
- Equipped with throughwiring, special PLUS version with 2 additional internal wires
- DALI2 driver compatible with 230V push dimming



Specifications

Item Code	Item Description	Equivalent to (W)	Power (W)	Lumen	Efficacy (lm/W)	CCT (K)	Internal wiring (mm ²)	Net Weight (kg/pc)
On-Off								
531000040500	LEDWaterproof-P5-L06-12/22W-840	TL 2x18W	11 - 22	1980/3630	165	4000	3x2.5	0.9
531000035400	LEDWaterproof-P5-L12-22/34W-840	TL 2x36W	22 - 34	3740/5780	170	4000	3x2.5	1.4
531000035600	LEDWaterproof-P5-L12-22/34W-840-PLUS	TL 2x36W	22 - 34	3740/5780	170	4000	5x2.5	1.4
531000041400	LEDWaterproof-P5-L12-22/34W-840/857	TL 2x36W	22 - 34	3740/5780	170	4K/5.7K	3x2.5	1.4
531000035900	LEDWaterproof-P5-L12-22/34W-857	TL 2x36W	22 - 34	3740/5780	170	4K/5.7K	3x2.5	1.4
531000036900	LEDWaterproof-P5-L15-28/42W-840	TL 2x58W	28 - 42	4760/7140	170	4000	3x2.5	1.8
531000037100	LEDWaterproof-P5-L15-28/42W-840/857	TL 2x58W	28 - 42	4760/7140	170	4K/5.7K	3x2.5	1.8
531000037500	LEDWaterproof-P5-L15-28/48W-840-PLUS	TL 2x58W	28 - 42	4760/8160	170	4000	5x2.5	1.8
531000037700	LEDWaterproof-P5-L15-42/48W-840	TL 2x58W	42 - 48	7140/8160	170	4000	3x2.5	1.8
531000037900	LEDWaterproof-P5-L15-42/48W-840/857	TL 2x58W	42 - 48	7140/8160	170	4K/5.7K	3x2.5	1.8
531000038100	LEDWaterproof-P5-L15-42/48W-857	TL 2x58W	42 - 48	7140/8160	170	5700	3x2.5	1.8
531000039100	LEDWaterproof-P5-L15-62/72W-840	TL 2x80W	62 - 72	10540/12240	170	4000	3x2.5	1.8
531000039700	LEDWaterproof-P5-L15-62/72W-857	TL 2x80W	62 - 72	10540/12240	170	5700	3x2.5	1.8
DALI2								
531000041200	LEDWaterproof-P5-L06-22W-DALI-840	TL 2x18W	22	3630	165	4000	5x2.5	0.9
531000036500	LEDWaterproof-P5-L12-34W-DALI-840	TL 2x36W	34	5780	170	4000	5x2.5	1.4
531000036700	LEDWaterproof-P5-L12-34W-DALI-857	TL 2x36W	34	5780	170	5700	5x2.5	1.4
531000038700	LEDWaterproof-P5-L15-48W-DALI-840	TL 2x58W	48	8160	170	4000	5x2.5	1.8
531000038900	LEDWaterproof-P5-L15-48W-DALI-857	TL 2x58W	48	8160	170	5700	5x2.5	1.8
531000040200	LEDWaterproof-P5-L15-72W-DALI-840	TL 2x80W	72	12240	170	4000	5x2.5	1.8
531000040400	LEDWaterproof-P5-L15-72W-DALI-857	TL 2x80W	72	12240	170	5700	5x2.5	1.8
Smart								
531000041000	LEDWaterproof-P5-L06-22W-BLE2-840	TL 2x18W	22	3630	165	4000	3x2.5	0.9
531000036100	LEDWaterproof-P5-L12-34W-BLE2-840	TL 2x36W	34	5780	170	4000	3x2.5	1.4

Item Code	Item Description	Equivalent to (W)	Power (W)	Lumen	Efficacy (lm/W)	CCT (K)	Internal wiring (mm ²)	Net Weight (kg/pc)
531000036300	LEDWaterproof-P5-L12-34W-BLE2-857	TL 2x36W	34	5780	170	5700	3x2.5	1.4
531000038300	LEDWaterproof-P5-L15-48W-BLE2-840	TL 2x58W	48	8160	170	4000	3x2.5	1.8
531000038500	LEDWaterproof-P5-L15-48W-BLE2-857	TL 2x58W	48	8160	170	5700	3x2.5	1.8
531000039900	LEDWaterproof-P5-L15-72W-BLE2-840	TL 2x80W	72	12240	170	4000	3x2.5	1.8
531000040100	LEDWaterproof-P5-L15-72W-BLE2-857	TL 2x80W	72	12240	170	5700	3x2.5	1.8
Tunable White/Smart								
531000036400	LEDWaterproof-P5-L12-34W-BLE2-TW	TL 2x36W	34	5780	170	3K-5.7K	3x2.5	1.4
531000038600	LEDWaterproof-P5-L15-48W-BLE2-TW	TL 2x58W	48	8160	170	3K-5.7K	3x2.5	1.8
Emergency kit 1 hour/On-Off								
531000040600	LEDWaterproof-P5-L06-12/22W-840-EM1	TL 2x18W	11 - 22	1980/3630	165	4000	4x2.5	1
Emergency kit 3 hour/On-Off								
531000035500	LEDWaterproof-P5-L12-22/34W-840-EM3	TL 2x36W	22 - 34	3740/5780	170	4000	4x2.5	1.7
531000035700	LEDWaterproof-P5-L12-22/34W-840-PLUS-EM3	TL 2x36W	22 - 34	3740/5780	170	4000	5x2.5	1.7
531000035800	LEDWaterproof-P5-L12-22/34W-840/857-EM3	TL 2x36W	22 - 34	3740/5780	170	4K/5.7K	4x2.5	1.7
531000036000	LEDWaterproof-P5-L12-22/34W-857-EM3	TL 2x36W	22 - 34	3740/5780	170	5700	4x2.5	1.7
531000037000	LEDWaterproof-P5-L15-28/42W-840-EM3	TL 2x58W	28 - 42	4760/7140	170	4000	4x2.5	2.1
531000037200	LEDWaterproof-P5-L15-28/42W-840/857-EM3	TL 2x58W	28 - 42	4760/7140	170	4K/5.7K	4x2.5	2.1
531000037600	LEDWaterproof-P5-L15-28/48W-840-PLUS-EM3	TL 2x58W	28 - 42	4760/8160	170	4000	5x2.5	2.1
531000037800	LEDWaterproof-P5-L15-42/48W-840-EM3	TL 2x58W	42 - 48	7140/8160	170	4000	4x2.5	2.1
531000038000	LEDWaterproof-P5-L15-42/48W-840/857-EM3	TL 2x58W	42 - 48	7140/8160	170	4K/5.7K	4x2.5	2.1
531000038200	LEDWaterproof-P5-L15-42/48W-857-EM3	TL 2x58W	42 - 48	7140/8160	170	5700	4x2.5	2.1
531000039200	LEDWaterproof-P5-L15-62/72W-840-EM3	TL 2x80W	62 - 72	10540/12240	170	4000	4x2.5	2.1
531000039800	LEDWaterproof-P5-L15-62/72W-857-EM3	TL 2x80W	62 - 72	10540/12240	170	5700	4x2.5	2.1
Emergency kit 3 hour/DALI2								
531000036600	LEDWaterproof-P5-L12-34W-DALI-840-EM3	TL 2x36W	34	5780	170	4000	5x2.5	1.7
531000038800	LEDWaterproof-P5-L15-48W-DALI-840-EM3	TL 2x58W	48	8160	170	4000	5x2.5	2.1
531000040300	LEDWaterproof-P5-L15-72W-DALI-840-EM3	TL 2x80W	72	12240	170	4000	5x2.5	2.1
Emergency kit 3 hour/Smart								
531000036200	LEDWaterproof-P5-L12-34W-BLE2-840-EM3	TL 2x36W	34	5780	170	4000	4x2.5	1.7
531000038400	LEDWaterproof-P5-L15-48W-BLE2-840-EM3	TL 2x58W	48	8160	170	4000	4x2.5	2.1
531000040000	LEDWaterproof-P5-L15-72W-BLE2-840-EM3	TL 2x80W	72	12240	170	4000	4x2.5	2.1

Technical Specifications

Lifetime (L70)	100,000 h
Lifetime (L80)	100,000 h
On-/Off-cycles	100,000
Colour consistency (SDCM)	4
Dimmability	On-Off / DALI2 / BLE2
Beam angle	120°
Finishing	Grey RAL 7035
Colour rendering index (CRI)	> 80
Ingress Protection (IP)	IP66
Impact strength (IK)	IK08
Protection class	II
Risk group (EN 62471)	RG0
With control gear	Yes
Glow wire test	850°C
Driver failure rate (at 5,000 hrs)	< 1%
Power factor	> 0.95
Input wire Ø (mm ²)	1mm ² - 2.5mm ²
Input cable Ø (mm ²)	7 - 15.5 mm ²

Electrical Supply

Frequency	50 - 60 Hz
Nominal voltage	220 - 240 V
DC input voltage	See catalogue appendix Connection Specifications

Mechanical Properties


Housing material	Polycarbonate
Mounting clips	Stainless steel

Ambient Conditions

Operating temperature	-30 - 45°C
Operating temperature (EM)	0 - 45°C
Application temperature	25°C
Storage environment	-30 - 60°C
Storage environment (EM)	0 - 60°C



Dimensional Drawing (mm)



Type	A	B	C	D
L600	600	680	73	71
L1200	1200	1280	73	71
L1500	1500	1580	73	71

Product Highlights

